Printing date 01/06/2023 Revised On 01/06/2023

1 Identification of the substance and manufacturer

Trade name: **SEMI GLOSS BLACK**

Product code: 0000110024

Recommended use: Paint and coatings application.

Uses advised against: Any that differs from the recommended use.

Manufacturer/Supplier: Seymour of Sycamore

917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101

www.seymourpaint.com

1-800-255-3924 **Emergency telephone number:**

Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482

www.seymourpaint.com

2 Hazard(s) identification

Classification of the substance or mixture

Flammable Aerosols 1 H222 Extremely flammable aerosol.

Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated.

Eye Irritation 2A H319 Causes serious eye irritation.

Toxic to Reproduction 1B H360 May damage fertility or the unborn child. Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information: **GHS Hazard pictograms**









GHS02 GHS04 GHS07 GHS08

Signal word Danger

Hazard statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation.

May damage fertility or the unborn child. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

Precautionary statements Obtain special instructions before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

Store in a well-ventilated place.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:		
67-64-1	Acetone	15-25%
	propane	15-25%
106-97-8		10-15%
	VM&P Naphtha	10-15%
	Mineral Spirits	5-10%
	Calcium Carbonate	1-5%
108-88-3		1-5%
67-63-0	Isopropyl Alcohol	1-5%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

Remove contaminated clothing. Wash exposed area with soap and water. After skin contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. After eye contact:

After swallowing: Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.

(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet

Printing date 01/06/2023 Revised On 01/06/2023

Trade name: SEMI GLOSS BLACK

Most important symptoms and

effects:

Dizziness

Indication of any immediate medical

attention needed:

No further relevant information available.

5 Fire-fighting measures

Extinguishing agents:

Special hazards:

Protective equipment for firefighters:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

No further relevant information available.

A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Dispose contaminated material as waste according to section 13.

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

67-64-1 Acetone

PEL (USA) Long-term value: 2400 mg/m³, 1000 ppm

REL (USA) Long-term value: 590 mg/m³, 250 ppm

TLV (USA) Short-term value: 500 ppm Long-term value: 250 ppm

A4, BEI

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm

REL (USA) Long-term value: 1800 mg/m³, 1000 ppm

TLV (USA) see Appendix F Minimal oxygen content (D, EX)

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm

TLV (USA) Short-term value: 1000 ppm

(EX)

108-88-3 Toluene

PEL (USA) Long-term value: 200 ppm

Ceiling limit value: 300; 500* ppm

*10-min peak per 8-hr shift

REL (USA) Short-term value: 560 mg/m³, 150 ppm

Long-term value: 375 mg/m³, 100 ppm

Long-term value: 20 ppm BEI, OTO, A4 TLV (USA)

67-63-0 Isopropyl Alcohol

PEL (USA) Long-term value: 980 mg/m³, 400 ppm

REL (USA) Short-term value: 1225 mg/m³, 500 ppm

Long-term value: 980 mg/m³, 400 ppm

TLV (USA) Short-term value: 400 ppm Long-term value: 200 ppm

BEI, A4

Ingredients with biological limit values:

67-64-1 Acetone

BEI (USA) 25 mg/L

Medium: urine

Time: end of shift

Parameter: Acetone (nonspecific)

(Contd. on page 3)

(Contd. of page 2)

Printing date 01/06/2023 Revised On 01/06/2023

Trade name: SEMI GLOSS BLACK

108-88-3 Toluene

BEI (USA) 0.02 mg/L

Medium: blood

Time: prior to last shift of workweek

Parameter: Toluene

0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene 0.3 mg/g creatinine Medium: urine

Time: end of shift Parameter: o-Cresol with hydrolysis (background)

67-63-0 Isopropyl Alcohol

BEI (USA) 40 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: Acetone (background, nonspecific)

Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use.

Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Store protective clothing separately. Avoid contact with the eyes and skin. Do not eat or drink while working.

Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In

cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygeine.

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Appearance: Aerosol. Odor: Aromatic Odor threshold: Not determined. pH-value: Not determined. Melting point/Melting range Undetermined. Boiling point: -110 °C (-166 °F) Flash point: -19 °C (-2.2 °F) Flammability (solid, gas): Extremely flammable.

Decomposition temperature: Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.7 Vol % 10.9 Vol % 10.9 Vol % Vapor pressure: Not determined. Vapor density Not applicable. Partition coefficient: n-octonal/water: Not determined. Solubility: Not determined. Viscosity: Not determined. Not determined.

Water: 0.0 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: No decomposition if used according to specifications.

Chemical stability: Not fully evaluated.

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials:
Hazardous decomposition:

No further relevant information available.
No dangerous decomposition products known.

(Contd. on page 4)

ı

Printing date 01/06/2023 Revised On 01/06/2023

Trade name: SEMI GLOSS BLACK

(Contd. of page 3)

11 Toxicological information

LD/LC50 values that are relevant for classification:

67-63-0 Isopropyl Alcohol

LD50 4,570 mg/kg (rat) Oral LD50 13,400 mg/kg (rab) Dermal Inhalative LC50/4 h 30 mg/l (rat)

Information on toxicological effects: No data available. Skin effects: No irritant effect. Eye effects: Irritating effect.

No sensitizing effects known. Sensitization:

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated Other information:

solvents.

Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available. Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled. Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

UN-Number UN1950 DOT UN1950

DOT Aerosols, flammable **ADR** 1950 Aerosols Transport hazard class(es):

2.1 Gases Class

Marine pollutant: No

Special precautions for user: Warning: Gases

EMS Number: F-D,S-U

Packaging Group:

UN1950, Aerosols, 2.1 **UN "Model Regulation":**

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-88-3 Toluene

67-63-0 Isopropyl Alcohol

Toxic Substances Control Act

All hazardous ingredients are found on the inventory list of substances. (TSCA):

Canadian Domestic Substances List

(DSL): Consumer Product Safety All ingredients are listed or exempted.

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

1333-86-4 Carbon black

100-41-4 ethyl benzene

Prop 65 chemicals known to cause birth defects or reproductive harm:

108-88-3 Toluene

EPA:

16 Other information

67-64-1 Acetone

Contact: Regulatory Affairs