

Safety Data Sheet

Copyright, 2019, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 07-7693-0
 Version Number:
 7.01

 Issue Date:
 01/25/19
 Supercedes Date:
 09/04/15

Product identifier

3MTM Rearview Mirror Adhesive, 08752

 ID Number
 UPC
 ID Number
 UPC

 60-4550-5186-6
 60-4550-6899-3
 00051135087527

7100019082

Recommended use

Automotive, Rearview Mirror Adhesive

Supplier's details

MANUFACTURER: 3M

DIVISION: Automotive Aftermarket

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

Telephone: 1-888-3M HELPS (1-888-364-3577)

Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS), Article Information Sheet (AIS), or Article Information Letter (AIL) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

07-7689-8, 07-7690-6

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued.3MMAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3Mproduct is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3Mproduct, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3Mproduct to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3Mprovides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information,3Mmakes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from3M

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2019, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 07-7689-8
 Version Number:
 8.01

 Issue Date:
 01/25/19
 Supercedes Date:
 11/03/14

SECTION 1: Identification

1.1. Product identifier

3MTM Rearview Mirror Adhesive / Adhesive, P/N 08752; 3MTM High Bond Rearview Mirror Adhesive / Adhesive, PN08749

Product Identification Numbers

ID Number UPC ID Number UPC

LB-K000-1110-0

1.2. Recommended use and restrictions on use

Recommended use

Adhesive, Rear View Mirror Adhesive

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Automotive Aftermarket

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 1.

Skin Corrosion/Irritation: Category 1B.

Skin Sensitizer: Category 1.

Specific Target Organ Toxicity (repeated exposure): Category 1. Specific Target Organ Toxicity (repeated exposure): Category 2.

2.2. Label elements

Signal word

Danger

Symbols

Corrosion | Exclamation mark | Health Hazard |





Hazard Statements

Causes severe skin burns and eye damage. May cause an allergic skin reaction.

Causes damage to organs through prolonged or repeated exposure:

nervous system | respiratory system |

May cause damage to organs through prolonged or repeated exposure:

skin

Precautionary Statements

General:

Keep out of reach of children.

Prevention:

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves, protective clothing, and eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

May cause chemical gastrointestinal burns.

36% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|--|---------------|------------------------|
| Aliphatic Urethane Acrylate Resin | Trade Secret* | 30 - 60 Trade Secret * |
| Bisphenol A Polyethylene Glycol Diether | 41637-38-1 | 10 - 30 Trade Secret * |
| Dimethacrylate | | |
| Hydroxypropyl Methacrylate | 27813-02-1 | 7 - 20 Trade Secret * |
| 1,6-Hexanediol Diacrylate | 13048-33-4 | 7 - 15 Trade Secret * |
| Isobornyl Acrylate | 5888-33-5 | 7 - 13 Trade Secret * |
| Acrylic Acid | 79-10-7 | 1 - 10 Trade Secret * |
| Polyester Resin | Trade Secret* | 5 - 10 Trade Secret * |
| 1-Acetyl-2-Phenylhydrazine | 114-83-0 | 0.1 - 1 Trade Secret * |
| 3-(Trimethoxysilyl)Propyl Glycidyl Ether | 2530-83-8 | 0.1 - 1 Trade Secret * |
| Cumene Hydroperoxide | 80-15-9 | 0.1 - 1 Trade Secret * |
| Saccharin | 81-07-2 | 0.1 - 1 Trade Secret * |

^{*}The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eve Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering

for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from oxidizing agents. Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|---------------------------|------------|--------|-----------------------|-------------------------|
| 1,6-Hexanediol Diacrylate | 13048-33-4 | AIHA | TWA:1 mg/m3(0.11 ppm) | Dermal Sensitizer |
| Acrylic Acid | 79-10-7 | ACGIH | TWA:2 ppm | SKIN, A4: Not class. as |
| | | | | human carcin |
| Cumene Hydroperoxide | 80-15-9 | AIHA | TWA:6 mg/m3(1 ppm) | SKIN |

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form: Liquid

Odor, Color, Grade: Yellow Liquid, Sharp Odor

Odor thresholdNo Data AvailablepHNot ApplicableMelting pointNo Data AvailableBoiling Point>=300 °F [@, 760 mmHg]

Flash Point >=200 °F [Test Method: Tagliabue Closed Cup]

Evaporation rateNo Data AvailableFlammability (solid, gas)Not ApplicableFlammable Limits(LEL)No Data AvailableFlammable Limits(UEL)No Data Available

Vapor Pressure >=5.0 mmHg [*Details*:CONDITIONS: @ 75 F.]

Vapor Density
Not Applicable
1.1 g/ml

Specific Gravity 1.1 [Ref Std:WATER=1]

Solubility In WaterNo Data AvailableSolubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNo Data Available

Decomposition temperatureNo Data AvailableViscosityNo Data Available

Hazardous Air Pollutants 1.08 lb HAPS/lb solids [Test Method:Calculated]

Molecular weight No Data Available

Volatile Organic Compounds21.1 % weight [Test Method:calculated per CARB title 2]Volatile Organic Compounds232 g/l [Test Method:calculated SCAQMD rule 443.1]

Percent volatile 21.1 % weight

VOC Less H2O & Exempt Solvents 232 g/l [*Test Method*:calculated SCAQMD rule 443.1]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Strong acids Strong oxidizing agents Amines

10.6. Hazardous decomposition products

SubstanceConditionCarbon monoxideNot SpecifiedCarbon dioxideNot Specified

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

May cause additional health effects (see below).

Eve Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

May cause additional health effects (see below).

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Dermal Effects: Signs/symptoms may include redness, itching, acne, or bumps on the skin.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--|---------------------------------------|-----------------------------------|--|
| Overall product | Dermal | | No data available; calculated ATE >5,000 mg/kg |
| Overall product | Inhalation- Vapor(4 hr) | | No data available; calculated ATE >50 mg/l |
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| Bisphenol A Polyethylene Glycol Diether Dimethacrylate | Dermal | Professio nal judgeme nt | LD50 estimated to be > 5,000 mg/kg |
| Bisphenol A Polyethylene Glycol Diether Dimethacrylate | Ingestion | Rat | LD50 > 2,000 mg/kg |
| 1,6-Hexanediol Diacrylate | Dermal | Rabbit | LD50 3,636 mg/kg |
| Hydroxypropyl Methacrylate | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| 1,6-Hexanediol Diacrylate | Ingestion | Rat | LD50 > 5,000 mg/kg |
| Hydroxypropyl Methacrylate | Ingestion | Rat | LD50 > 2,000 mg/kg |
| Isobornyl Acrylate | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| Isobornyl Acrylate | Ingestion | Rat | LD50 4,350 mg/kg |
| Acrylic Acid | Dermal | Rabbit | LD50 > 2,000 mg/kg |
| Acrylic Acid | Inhalation- Dust/Mist (4 hours) | Rat | LC50 3.8 mg/l |
| Acrylic Acid | Ingestion | Rat | LD50 1,250 mg/kg |
| 1-Acetyl-2-Phenylhydrazine | Dermal | | LD50 estimated to be 200 - 1,000 mg/kg |
| Saccharin | Dermal | | LD50 estimated to be > 5,000 mg/kg |

Page 7 of 12

| 1-Acetyl-2-Phenylhydrazine | Ingestion | Mouse | LD50 270 mg/kg |
|--|-------------|--------|-------------------|
| Saccharin | Ingestion | Mouse | LD50 17,000 mg/kg |
| 3-(Trimethoxysilyl)Propyl Glycidyl Ether | Dermal | Rabbit | LD50 4,000 mg/kg |
| 3-(Trimethoxysilyl)Propyl Glycidyl Ether | Inhalation- | Rat | LC50 > 5.3 mg/l |
| | Dust/Mist | | |
| | (4 hours) | | |
| 3-(Trimethoxysilyl)Propyl Glycidyl Ether | Ingestion | Rat | LD50 7,010 mg/kg |
| Cumene Hydroperoxide | Dermal | Rat | LD50 500 mg/kg |
| Cumene Hydroperoxide | Inhalation- | Rat | LC50 1.4 mg/l |
| | Vapor (4 | | |
| | hours) | | |
| Cumene Hydroperoxide | Ingestion | Rat | LD50 382 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|--|---------|--------------------|
| | | |
| 1,6-Hexanediol Diacrylate | Rabbit | Irritant |
| Hydroxypropyl Methacrylate | Rabbit | Minimal irritation |
| Isobornyl Acrylate | Rabbit | Minimal irritation |
| Acrylic Acid | Rabbit | Corrosive |
| 3-(Trimethoxysilyl)Propyl Glycidyl Ether | Rabbit | Mild irritant |
| Cumene Hydroperoxide | Rabbit | Corrosive |

Serious Eye Damage/Irritation

| Name | Species | Value |
|--|---------|-------------------|
| | | |
| 1,6-Hexanediol Diacrylate | Rabbit | Moderate irritant |
| Hydroxypropyl Methacrylate | Rabbit | Moderate irritant |
| Isobornyl Acrylate | Rabbit | Mild irritant |
| Acrylic Acid | Rabbit | Corrosive |
| 3-(Trimethoxysilyl)Propyl Glycidyl Ether | Rabbit | Corrosive |
| Cumene Hydroperoxide | Rabbit | Corrosive |

Skin Sensitization

| Name | Species | Value |
|--|---------|----------------|
| Bisphenol A Polyethylene Glycol Diether Dimethacrylate | Guinea | Not classified |
| | pig | |
| 1,6-Hexanediol Diacrylate | Guinea | Sensitizing |
| | pig | |
| Hydroxypropyl Methacrylate | Human | Sensitizing |
| | and | |
| | animal | |
| Isobornyl Acrylate | Mouse | Sensitizing |
| Acrylic Acid | Guinea | Not classified |
| | pig | |
| 3-(Trimethoxysilyl)Propyl Glycidyl Ether | Guinea | Not classified |
| | pig | |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|--|----------|--|
| | | |
| Bisphenol A Polyethylene Glycol Diether Dimethacrylate | In Vitro | Not mutagenic |
| 1,6-Hexanediol Diacrylate | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Hydroxypropyl Methacrylate | In vivo | Not mutagenic |
| Hydroxypropyl Methacrylate | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Isobornyl Acrylate | In Vitro | Some positive data exist, but the data are not |

Page 8 of 12

| | | sufficient for classification |
|--|----------|--|
| Acrylic Acid | In vivo | Not mutagenic |
| Acrylic Acid | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| 3-(Trimethoxysilyl)Propyl Glycidyl Ether | In vivo | Not mutagenic |
| 3-(Trimethoxysilyl)Propyl Glycidyl Ether | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Cumene Hydroperoxide | In vivo | Not mutagenic |
| Cumene Hydroperoxide | In Vitro | Some positive data exist, but the data are not sufficient for classification |

Carcinogenicity

| Name | Route | Species | Value |
|--|------------|----------|--|
| 1,6-Hexanediol Diacrylate | Dermal | Mouse | Not carcinogenic |
| Hydroxypropyl Methacrylate | Inhalation | Multiple | Not carcinogenic |
| | | animal | |
| | | species | |
| Acrylic Acid | Ingestion | Rat | Not carcinogenic |
| Acrylic Acid | Dermal | Mouse | Some positive data exist, but the data are not |
| | | | sufficient for classification |
| 3-(Trimethoxysilyl)Propyl Glycidyl Ether | Dermal | Mouse | Not carcinogenic |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|--|------------------|--|---------|--------------------------|-----------------------------|
| 1,6-Hexanediol Diacrylate | Not Specified | Not classified for development | Rat | NOAEL 750 mg/kg/day | during organogenesi s |
| Hydroxypropyl Methacrylate | Ingestion | Not classified for female reproduction | Rat | NOAEL 1,000 mg/kg/day | premating into lactation |
| Hydroxypropyl Methacrylate | Ingestion | Not classified for male reproduction | Rat | NOAEL 1,000 mg/kg/day | 49 days |
| Hydroxypropyl Methacrylate | Ingestion | Not classified for development | Rat | NOAEL 1,000 mg/kg/day | during gestation |
| Acrylic Acid | Ingestion | Not classified for female reproduction | Rat | NOAEL 460 mg/kg/day | 2 generation |
| Acrylic Acid | Ingestion | Not classified for male reproduction | Rat | NOAEL 460 mg/kg/day | 2 generation |
| Acrylic Acid | Inhalation | Not classified for development | Rat | NOAEL 1.1 mg/l | during organogenesi s |
| Acrylic Acid | Ingestion | Not classified for development | Rat | NOAEL 53 mg/kg/day | 2 generation |
| 3-(Trimethoxysilyl)Propyl Glycidyl Ether | Ingestion | Not classified for female reproduction | Rat | NOAEL 1,000 mg/kg/day | 1 generation |
| 3-(Trimethoxysilyl)Propyl Glycidyl Ether | Ingestion | Not classified for male reproduction | Rat | NOAEL 1,000 mg/kg/day | 1 generation |
| 3-(Trimethoxysilyl)Propyl Glycidyl Ether | Ingestion | Not classified for development | Rat | NOAEL 3,000 mg/kg/day | during organogenesi s |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|-------------------------------|------------|------------------------|--|------------------------------|------------------------|----------------------|
| 1,6-Hexanediol Diacrylate | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | |
| Hydroxypropyl Methacrylate | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL Not available | |

Page 9 **of** 12

| Isobornyl Acrylate | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | official classifica tion | NOAEL Not available | |
|----------------------|------------|--------------------------------------|--|-----------------------------------|------------------------|-----------------------|
| Acrylic Acid | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | |
| Cumene Hydroperoxide | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | occupational exposure |
| Cumene Hydroperoxide | Inhalation | respiratory irritation | May cause respiratory irritation | Human | NOAEL Not available | occupational exposure |
| Cumene Hydroperoxide | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Professio nal judgeme nt | NOAEL Not available | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---|------------|--|--|---------|-----------------------------|----------------------|
| 1,6-Hexanediol Diacrylate | Dermal | skin | May cause damage to organs though prolonged or repeated exposure | Mouse | LOAEL 70 mg/kg/day | 80 weeks |
| Hydroxypropyl Methacrylate | Inhalation | blood | Not classified | Rat | NOAEL 0.5 mg/l | 21 days |
| Hydroxypropyl Methacrylate | Ingestion | hematopoietic system heart endocrine system liver immune system nervous system kidney and/or bladder | Not classified | Rat | NOAEL 1,000 mg/kg/day | 41 days |
| 3-(Trimethoxysilyl)Propyl Glycidyl Ether | Ingestion | heart endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system kidney and/or bladder respiratory system | Not classified | Rat | NOAEL 1,000 mg/kg/day | 28 days |
| Cumene Hydroperoxide | Inhalation | nervous system respiratory system | Causes damage to organs through prolonged or repeated exposure | Rat | LOAEL 0.2 mg/l | 7 days |
| Cumene Hydroperoxide | Inhalation | heart liver kidney and/or bladder | Not classified | Rat | NOAEL 0.03 mg/l | 90 days |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

Page 10 **of** 12

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

| Physical Hazards | |
|------------------|--|
| Not applicable | |

Health Hazards

Hazard Not Otherwise Classified (HNOC)

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

Skin Corrosion or Irritation

Specific target organ toxicity (single or repeated exposure)

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

| <u>Ingredient</u> | <u>C.A.S. No</u> | <u>% by Wt</u> | |
|----------------------|------------------|----------------|---------|
| Acrylic Acid | 79-10-7 | Trade Secret | 1 - 10 |
| Cumene Hydroperoxide | 80-15-9 | Trade Secret | 0.1 - 1 |
| Saccharin | 81-07-2 | Trade Secret | 0.1 - 1 |

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Page 11 **of** 12

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 Flammability: 1 Instability: 1 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 07-7689-8
 Version Number:
 8.01

 Issue Date:
 01/25/19
 Supercedes Date:
 11/03/14

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued.3MMAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3Mproduct is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3Mproduct, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3Mproduct to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3Mprovides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information,3Mmakes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from3M

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2022, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 07-7690-6
 Version Number:
 7.02

 Issue Date:
 07/13/22
 Supercedes Date:
 05/24/18

SECTION 1: Identification

1.1. Product identifier

3MTM Rearview Mirror Adhesive (Primer), PN08752; 3MTM High Bond Rearview Mirror Adhesive (Primer), PN08749

Product Identification Numbers

ID Number UPC ID Number UPC

LB-K000-1119-0

1.2. Recommended use and restrictions on use

Recommended use

Adhesive, Rear View Mirror Adhesive - Primer

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Construction and Home Improvement Markets **ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA **Telephone:** 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification

Flammable Liquid: Category 2.

Serious Eye Damage/Irritation: Category 2A.

Specific Target Organ Toxicity (single exposure): Category 3.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Exclamation mark |

Pictograms





Hazard Statements

Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Precautionary Statements

General:

Keep out of reach of children.

Prevention:

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Keep container tightly closed.

Use explosion-proof electrical/ventilating/lighting equipment.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves and eye/face protection.

Wash thoroughly after handling.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Call a POISON CENTER or doctor/physician if you feel unwell.

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place. Keep cool.

Keep container tightly closed.

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2% of the mixture consists of ingredients of unknown acute dermal toxicity.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|---|------------|-------------------------|
| Isopropyl Alcohol | 67-63-0 | 60 - 100 Trade Secret * |
| Stoddard Solvent | 8052-41-3 | 1 - 5 Trade Secret * |
| Carboxylic acids, C3-10, copper(1+) salts, oxidized | 85737-14-0 | <= 1 Trade Secret * |

Page 2 of 11

| Neodecanoic acid, copper(2+) salt | 68084-48-0 | <= 1 Trade Secret * |
|-----------------------------------|------------|---------------------|
| Organo Copper Compound | 22221-10-9 | <= 1 Trade Secret * |

^{*}The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eve Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire extinguishing foam that is resistant to polar solvents. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from acids. Store away from oxidizing agents. Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|-------------------|------------|--------|--------------------------|----------------------------|
| COPPER COMPOUNDS | 22221-10-9 | ACGIH | TWA(as Cu, fume):0.2 | |
| | | | mg/m3;TWA(as Cu dust or | |
| | | | mist):1 mg/m3 | |
| Isopropyl Alcohol | 67-63-0 | ACGIH | TWA:200 ppm;STEL:400 ppm | A4: Not class. as human |
| | | | | carcin |
| Isopropyl Alcohol | 67-63-0 | OSHA | TWA:980 mg/m3(400 ppm) | |
| COPPER COMPOUNDS | 68084-48-0 | ACGIH | TWA(as Cu, fume):0.2 | |
| | | | mg/m3;TWA(as Cu dust or | |
| | | | mist):1 mg/m3 | |
| Stoddard Solvent | 8052-41-3 | ACGIH | TWA:100 ppm | |
| Stoddard Solvent | 8052-41-3 | OSHA | TWA:2900 mg/m3(500 ppm) | |
| COPPER COMPOUNDS | 85737-14-0 | ACGIH | TWA(as Cu, fume):0.2 | |
| | | | mg/m3;TWA(as Cu dust or | |
| | | | mist):1 mg/m3 | |

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines
OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

Page 4 of

11

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Fluoroelastomer

Nitrile Rubber Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state Liquid Color Colorless

Odor Mild Organic solvent
Odor threshold No Data Available

pH Not Applicable
Melting point Not Applicable
Boiling Point 180 °F

Flash Point 53.0 °F [Test Method: Tagliabue Closed Cup]

Evaporation rate 7.7

Flammability (solid, gas)

Flammable Limits(LEL)

Flammable Limits(UEL)

12.0 %

Vapor Pressure 32.0 mmHg [*Details*:CONDITIONS: @ 68 F.]

Vapor Density 2.1 [Ref Std: AIR=1]

Density 0.79 g/ml

Specific Gravity 0.79 [Ref Std:WATER=1]

Solubility In Water 95 - 100 %

Solubility in Water Moderate

Solubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNo Data AvailableDecomposition temperatureNo Data AvailableViscosity3 centipoise

Hazardous Air Pollutants 0 lb HAPS/lb solids [Test Method: Calculated]

Molecular weight No Data Available

Volatile Organic Compounds
783 g/l [Test Method:calculated SCAQMD rule 443.1]
Volatile Organic Compounds
99.1 % weight [Test Method:calculated per CARB title 2]

Percent volatile 98.51 % weight

VOC Less H2O & Exempt Solvents 783 g/l [Test Method:calculated SCAQMD rule 443.1]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong acids Strong oxidizing agents Amines

10.6. Hazardous decomposition products

SubstanceConditionCarbon monoxideNot SpecifiedCarbon dioxideNot Specified

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eve Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|---|-----------------------------------|---------|---|
| Overall product | Dermal | | No data available; calculated ATE >5,000 mg/kg |
| Overall product | Ingestion | | No data available; calculated ATE >2,000 - =5,000 mg/kg |
| Isopropyl Alcohol | Dermal | Rabbit | LD50 12,870 mg/kg |
| Isopropyl Alcohol | Inhalation- Vapor (4 hours) | Rat | LC50 72.6 mg/l |
| Isopropyl Alcohol | Ingestion | Rat | LD50 4,710 mg/kg |
| Stoddard Solvent | Inhalation- Vapor | | LC50 estimated to be 20 - 50 mg/l |
| Stoddard Solvent | Dermal | Rabbit | LD50 > 3,000 mg/kg |
| Stoddard Solvent | Ingestion | Rat | LD50 > 5,000 mg/kg |
| Carboxylic acids, C3-10, copper(1+) salts, oxidized | Ingestion | | LD50 estimated to be 300 - 2,000 mg/kg |
| Neodecanoic acid, copper(2+) salt | Dermal | | LD50 estimated to be 2,000 - 5,000 mg/kg |
| Neodecanoic acid, copper(2+) salt | Ingestion | | LD50 estimated to be 2,000 - 5,000 mg/kg |
| Organo Copper Compound | Ingestion | | LD50 estimated to be 300 - 2,000 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|-------------------|-------------------------------|---------------------------|
| Isopropyl Alcohol | Multiple animal species | No significant irritation |
| Stoddard Solvent | Rabbit | Irritant |

Serious Eye Damage/Irritation

| Serious Eye Bumuger Himation | | |
|------------------------------|---------|-----------------|
| Name | Species | Value |
| Isopropyl Alcohol | Rabbit | Severe irritant |

Page 7 **of** 11

| Stoddard Solvent | Rabbit | No significant irritation |
|------------------|--------|---------------------------|
|------------------|--------|---------------------------|

Skin Sensitization

| Name | Species | Value |
|-------------------|---------|----------------|
| Isopropyl Alcohol | Guinea | Not classified |
| | pig | |
| Stoddard Solvent | Guinea | Not classified |
| | pig | |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Germ Cen Mutagementy | | |
|----------------------|----------|--|
| Name | Route | Value |
| | | |
| Isopropyl Alcohol | In Vitro | Not mutagenic |
| Isopropyl Alcohol | In vivo | Not mutagenic |
| Stoddard Solvent | In vivo | Not mutagenic |
| Stoddard Solvent | In Vitro | Some positive data exist, but the data are not sufficient for classification |

Carcinogenicity

| Name | Route | Species | Value |
|-------------------|------------|------------------------|--|
| Isopropyl Alcohol | Inhalation | Rat | Some positive data exist, but the data are not sufficient for classification |
| Stoddard Solvent | Dermal | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Stoddard Solvent | Inhalation | Human and animal | Some positive data exist, but the data are not sufficient for classification |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|-------------------|------------|--------------------------------|---------|------------------------|-----------------------------|
| Isopropyl Alcohol | Ingestion | Not classified for development | Rat | NOAEL 400 mg/kg/day | during organogenesi s |
| Isopropyl Alcohol | Inhalation | Not classified for development | Rat | LOAEL 9 mg/l | during gestation |
| Stoddard Solvent | Inhalation | Not classified for development | Rat | NOAEL 2.4 mg/l | during organogenesi s |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|-------------------|------------|--------------------------------------|--|------------------------|------------------------|---------------------------|
| Isopropyl Alcohol | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | |
| Isopropyl Alcohol | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | |
| Isopropyl Alcohol | Inhalation | auditory system | Not classified | Guinea pig | NOAEL 13.4 mg/l | 24 hours |
| Isopropyl Alcohol | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | poisoning and/or abuse |
| Stoddard Solvent | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human and animal | NOAEL Not available | |

Page 8 **of** 11

| Stoddard Solvent | Inhalation | respiratory irritation | Some positive data exist, but the | | NOAEL Not | |
|------------------|------------|------------------------|-----------------------------------|-----------|-----------|---------|
| | | | data are not sufficient for | | available | |
| | | | classification | | | |
| Stoddard Solvent | Inhalation | nervous system | Not classified | Dog | NOAEL 6.5 | 4 hours |
| | | | | | mg/l | |
| Stoddard Solvent | Ingestion | central nervous | May cause drowsiness or | Professio | NOAEL Not | |
| | | system depression | dizziness | nal | available | |
| | | | | judgeme | | |
| | | | | nt | | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|-------------------|------------|---|----------------|-------------------------------|------------------------|----------------------|
| Isopropyl Alcohol | Inhalation | kidney and/or bladder | Not classified | Rat | NOAEL 12.3 mg/l | 24 months |
| Isopropyl Alcohol | Inhalation | nervous system | Not classified | Rat | NOAEL 12 mg/l | 13 weeks |
| Isopropyl Alcohol | Ingestion | kidney and/or bladder | Not classified | Rat | NOAEL 400 mg/kg/day | 12 weeks |
| Stoddard Solvent | Inhalation | nervous system | Not classified | Rat | LOAEL 4.6 mg/l | 6 months |
| Stoddard Solvent | Inhalation | kidney and/or bladder | Not classified | Rat | LOAEL 1.9 mg/l | 13 weeks |
| Stoddard Solvent | Inhalation | respiratory system | Not classified | Multiple animal species | NOAEL 0.6 mg/l | 90 days |
| Stoddard Solvent | Inhalation | bone, teeth, nails, and/or hair blood liver muscles | Not classified | Rat | NOAEL 5.6 mg/l | 12 weeks |
| Stoddard Solvent | Inhalation | heart | Not classified | Multiple animal species | NOAEL 1.3 mg/l | 90 days |

Aspiration Hazard

| Name | Value |
|------------------|-------------------|
| Stoddard Solvent | Aspiration hazard |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective

regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Flammable (gases, aerosols, liquids, or solids)

Health Hazards

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 3 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 07-7690-6
 Version Number:
 7.02

 Issue Date:
 07/13/22
 Supercedes Date:
 05/24/18

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to

Page 10 of 1

determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com