

SECTION 1. IDENTIFICATION

Product identifier

Chemical Name Mixture
CAS No. Mixture
Trade Name Hand Sanitizer

Product Codes 8-HS-PR, 8-HS-SPRY, 4-HS-DP, 128-HS

Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s) Hand Sanitizer

Uses Advised Against None

Company Identification The B'laster Corporation

8500 Sweet Valley Drive Valley View, OH 44125

Telephone (216) 901-5800 Fax (216) 901-5801

Emergency telephone number

Emergency Phone No. CHEMTREC 24 hr. 1-800-424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Hand Sanitizer

Restrictions on use None know

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Eye irritation : Category 2A

GHS Label element

Hazard pictograms :





Signal Word : Warning

Hazard Statements : H226 Flammable liquid and vapor.

H319 Causes serious eye irritation.



Precautionary Statements

: Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P241 Use explosion-proof electrical/ ventilating/ lighting/

equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately

all contaminated clothing. Rinse skin with water/shower. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards

Vapors may form explosive mixture with air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical Name	CAS-No.	Concentration (%) v/v
Ethanol	64-17-5	80
Glycerol	56-81-5	1.45
Hydrogen peroxide	7722-84-1	0.125

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.



If swallowed : If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur.

Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delayed

: Causes serious eye irritation.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment

when the potential for exposure exists.

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam

Dry chemical

Carbon dioxide (CO2)

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during fire

fighting

: Do not use a solid water stream as it may scatter and spread

fire.

Flash back possible over considerable distance. Vapors may form explosive mixtures with air.

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod-

ucts

: Carbon oxides

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment

for fire-fighters

: In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.

Use personal protective equipment.

Follow safe handling advice and personal protective

equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided.



Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Non-sparking tools should be used.

Soak up with inert absorbent material.

Suppress (knock down) gases/vapors/mists with a water spray

jet.

For large spills, provide diking or other appropriate

containment to keep material from spreading. If diked material

can be pumped, store recovered material in appropriate

container.

Clean up remaining materials from spill with suitable

absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use with local exhaust ventilation.

Use only in an area equipped with explosion proof exhaust

ventilation.

Advice on safe handling : Do not breathe vapors or spray mist.

Do not swallow. Do not get in eyes.

Avoid prolonged or repeated contact with skin.

Handle in accordance with good industrial hygiene and safety

practice.

Non-sparking tools should be used. Keep container tightly closed.

Keep away from heat and sources of ignition.

Take precautionary measures against static discharges.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Keep tightly closed.

Keep in a cool, well-ventilated place.

Store in accordance with the particular national regulations.

Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents



Organic peroxides Flammable solids Pyrophoric liquids

Pyrophoric solids

Self-heating substances and mixtures

Substances and mixtures which in contact with water emit

flammable gases

Explosives

Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ethanol	64-17-5	TWA	1,000 ppm 1,900 mg/m3	NIOSH REL
Ethanol	64-17-5	TWA	1,000 ppm 1,900 mg/m3	OSHA Z-1
Ethanol	64-17-5	STEL	1,000 ppm	ACGIH

Engineering measures : Minimize workplace exposure concentrations.

Use only in an area equipped with explosion proof exhaust

ventilation.

Use with local exhaust ventilation.

Personal protective equipment

Respiratory protection General and

local exhaust ventilation is recommended to maintain vapor



Hand protection

Material : Impervious gloves

Material : Flame retardant gloves

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before

breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:

Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Wear the following personal protective equipment:

Flame retardant antistatic protective clothing.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Hygiene measures : Ensure that eye flushing systems and safety showers are

located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : clear,

Odor : Alcohol

Odor Threshold : No data available

pH : 6.5 - 8.5

Melting point/freezing point : No data available

Initial boiling point and boiling

range

: 73 °C



Flash point : 25 °C

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

Density : 0.881 g/cm3

Solubility(ies)

Water solubility : soluble

Partition coefficient: n-

octanol/water

: Not applicable

Autoignition temperature : No data available

Decomposition temperature : The substance or mixture is not classified self-reactive.

Viscosity

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

: Flammable liquid and vapor.

Vapors may form explosive mixture with air. Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

: No hazardous decomposition products are known.



SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Ingredients:

Ethanol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 124.7 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Propan-2-ol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 72.6 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Result: No skin irritation

<u>Ingredients:</u>

Ethanol:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Ingredients:



Ethanol:

Species: Rabbit

Result: Irritation to eyes, reversing within 21 days

Method: OECD Test Guideline 405

Respiratory or skin sensitization

Skin sensitization: Not classified based on available information.

Respiratory sensitization: Not classified based on available information.

Product:

Assessment: Does not cause skin sensitization.

Ingredients:

Ethanol:

Test Type: Local lymph node assay (LLNA)

Routes of exposure: Skin contact

Species: Mouse Result: negative

Germ cell mutagenicity

Not classified based on available information.

Ingredients:

Ethanol:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)

Species: Mouse

Application Route: Ingestion

Result: negative



IARC No ingredient of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHANo ingredient of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential carcino-

gen by OSHA.

NTP No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Not classified based on available information.

Ingredients:

Ethanol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Mouse

Application Route: Ingestion Method: OECD Test Guideline 416

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion

Result: negative

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Ingredients:

Ethanol:

Species: Rat NOAEL: 2,400

mg/kg

Application Route: Ingestion Exposure

time: 2 y

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Ingredients:

Ethanol:



Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 1,000 mg/l

Exposure time: 48 h

Toxicity to algae : EC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC (Daphnia magna (Water flea)): 9.6 mg/l

Exposure time: 9 d

Toxicity to bacteria : EC50 (Photobacterium phosphoreum): 32.1 mg/l

Exposure time: 0.25 h

Persistence and degradability

Ingredients:

Ethanol:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 84 % Exposure time: 20 d

Bioaccumulative potential

Ingredients:

Ethanol:

Partition coefficient: n-

octanol/water

: log Pow: -0.35

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Dispose of as unused product.

Empty containers should be taken to an approved waste

handling site for recycling or disposal.

Do not burn, or use a cutting torch on, the empty drum.



SECTION 14. TRANSPORT INFORMATION

Domestic regulation

DOT 49 CFR

UN/ID/NA number : UN 1987

Proper shipping name : ALCOHOLS, N.O.S. LTD

QTY

Class : 3 Packing group : III

Labels : LTD QTY
ERG Code : 127
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard

Acute Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

None

US State Regulations Pennsylvania

Right To Know

Ethanol 64-17-5 75- 90 % Water 7732-18-5 10 - 30 %

New Jersey Right To Know

Ethanol 64-17-5 75 - 90 % Water 7732-18-5 10 - 30 %

California Prop 65 This product does not contain any chemicals known to the

State of California to cause cancer, birth, or any other

reproductive defects.

The ingredients of this product are reported in the following inventories:



REACH : All ingredients (pre-)registered or exempt.

TSCA : All chemical substances in this material are included on or

exempted from listing on the TSCA Inventory of Chemical

Substances.

DSL : All chemical substances in this product comply with the CEPA

1999 and NSNR and are on or exempt from listing on the

Canadian Domestic Substances List (DSL).

AICS : All ingredients listed or exempt.


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), NECSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

NFPA:



HMIS III:

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High 4 = Extreme, * = Chronic

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV) ACGIH - Biological Exposure Indices (BEI) ACGIH BEI **NIOSH REL** : USA. NIOSH Recommended Exposure Limits

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

OSHA Z-1 / TWA : 8-hour time weighted average



Revision Date : 03/26/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.