Safety Data Sheet

Printing date 01/09/2023 Revised On 01/09/2023

1 Identification of the substance and manufacturer

Trade name: **GREEN ZINC PHOSPHATE**

0000160899 Product code:

Recommended use: Paint and coatings application.

Uses advised against: Any that differs from the recommended use.

Seymour of Sycamore Manufacturer/Supplier:

917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101

www.seymourpaint.com

1-800-255-3924 **Emergency telephone number:**

Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482

www.seymourpaint.com

2 Hazard(s) identification

Classification of the substance or mixture

Flammable Aerosols 1 H222 Extremely flammable aerosol.

Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated.

Eye Irritation 2A H319 Causes serious eye irritation. Sensitization - Skin 1 H317 May cause an allergic skin reaction. Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information: **GHS Hazard pictograms**

Precautionary statements







GHS02 GHS04 GHS07 GHS08

Signal word Danger

Hazard statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.
Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

If eye irritation persists: Get medical advice/attention.

Store in a well-ventilated place.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:		
	methyl acetate	25-50%
	propane	15-25%
	n-butane	5-10%
	Isobutyl Acetate	1-5%
1330-20-7	xylene (mix)	1-5%
	ethyl alcohol	1-5%
	Acetone	1-5%
	VM&P Naphtha	1-5%
	Mineral Spirits	1-5%
	methanol	0.17%
108-31-6	maleic anhydride	0.03%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

Remove contaminated clothing. Wash exposed area with soap and water. After skin contact:

(Contd. on page 2)

Safety Data Sheet

Printing date 01/09/2023 Revised On 01/09/2023

Trade name: GREEN ZINC PHOSPHATE

(Contd. of page 1)

After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. After swallowing:

Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.

Most important symptoms and

effects:

Indication of any immediate medical

attention needed:

Dizziness

No further relevant information available.

5 Fire-fighting measures

Extinguishing agents:

Special hazards:

Protective equipment for

firefighters:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

No further relevant information available.

A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up:

Ensure adequate ventilation.

7 Handling and storage

Precautions for safe handling Storage requirements:

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

79-20-9 methyl acetate

PEL (USA) Long-term value: 610 mg/m³, 200 ppm REL (USA) Short-term value: 760 mg/m³, 250 ppm

Long-term value: 610 mg/m³, 200 ppm

Short-term value: 250 ppm Long-term value: 200 ppm TLV (USA)

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm

REL (USA) Long-term value: 1800 mg/m³, 1000 ppm

TLV (USA) see Appendix F Minimal oxygen content (D, EX)

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm

TLV (USA) Short-term value: 1000 ppm

(EX)

110-19-0 Isobutyl Acetate

PEL (USA) Long-term value: 700 mg/m³, 150 ppm

REL (USA) Long-term value: 700 mg/m³, 150 ppm

TLV (USA) Short-term value: 150 ppm Long-term value: 50 ppm

1330-20-7 xylene (mix)

PEL (USA) Long-term value: 435 mg/m³, 100 ppm

REL (USA) Short-term value: 655 mg/m³, 150 ppm

Long-term value: 435 mg/m³, 100 ppm

TLV (USA) Long-term value: 20 ppm

BEI, A4

64-17-5 ethyl alcohol

PEL (USA) Long-term value: 1900 mg/m³, 1000 ppm

REL (USA) Long-term value: 1900 mg/m³, 1000 ppm

TLV (USA) | Short-term value: 1000 ppm

A3

67-64-1 Acetone

PEL (USA) Long-term value: 2400 mg/m³, 1000 ppm

REL (USA) Long-term value: 590 mg/m³, 250 ppm

TLV (USA) Short-term value: 500 ppm

Long-term value: 250 ppm

A4, BEI

(Contd. on page 3)

Printing date 01/09/2023 Revised On 01/09/2023

Trade name: GREEN ZINC PHOSPHATE

67-56-1 methanol (Contd. of page 2)

PEL (USA) Long-term value: 260 mg/m³, 200 ppm

REL (USA) Short-term value: 325 mg/m³, 250 ppm Long-term value: 260 mg/m³, 200 ppm

Skin

TLV (USA) Short-term value: 250 ppm

Long-term value: 200 ppm

Skin; BEI

108-31-6 maleic anhydride

PEL (USA) Long-term value: 1 mg/m³, 0.25 ppm REL (USA) Long-term value: 1 mg/m³, 0.25 ppm TLV (USA) Long-term value: 0.01* mg/m³

DSEN, RSEN;*inh. fraction + vapor, A4

Ingredients with biological limit values:

1330-20-7 xylene (mix)

BEI (USA) 1.5 g/g creatinine Medium: urine Time: end of shift

Parameter: Methylhippuric acids

67-64-1 Acetone

BEI (USA) 25 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

67-56-1 methanol

BEI (USA) 15 mg/L

Medium: urine Time: end of shift

Parameter: Methanol (background, nonspecific)

Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use.

Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Avoid contact with the eyes and skin. Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In

cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygeine.

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Appearance:Aerosol.Odor:AromaticOdor threshold:Not determined.

pH-value:
Melting point/Melting range
Boiling point:

Flash point:

Flammability (solid, gas):

Not determined.
Undetermined.
-110 °C (-166 °F)
-19 °C (-2.2 °F)
Extremely flammable.

Decomposition temperature: Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.7 Vol % 16 Vol %

Vapor pressure: Not determined. Vapor density Not applicable. Partition coefficient: n-octonal/water: Not determined. Solubility: Not determined. Not determined.

Water: 0.0 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: No decomposition if used according to specifications.

Chemical stability: Not fully evaluated.

(Contd. on page 4)

(Contd. of page 3)

Printing date 01/09/2023 Revised On 01/09/2023

Trade name: GREEN ZINC PHOSPHATE

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

	•			
LD/LC50 values that are relevant for classification:				
79-20-9 methyl acetate				
Oral	LD50	6,970 mg/kg (rat)		
110-19-0 Isobutyl Acetate				
Oral	LD50	4,763 mg/kg (rbt)		
1330-20-7 xylene (mix)				
Oral	LD50	8,700 mg/kg (rat)		
Dermal	LD50	2,000 mg/kg (rbt)		
Inhalative	LC50/4 h	6,350 mg/l (rat)		
64-17-5 ethyl alcohol				
Oral	LD50	7,060 mg/kg (rat)		
Inhalative	LC50/4 h	20,000 mg/l (rat)		
67-56-1 methanol				
Oral	LD50	5.628 mg/kg (rat)		

Dermal LD50 15,800 mg/kg (rbt)

Information on toxicological effects: No data available. Skin effects: No irritant effect. Eye effects: Irritating effect.

No sensitizing effects known. Sensitization:

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

Other information:

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated

solvents.

No further relevant information available. Bioaccumulative potential: Mobility in soil: No further relevant information available. No further relevant information available. Other adverse effects:

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

UN1950 **UN-Number** DOT UN1950 UN1950

DOT Aerosols, flammable **ADR** 1950 Aerosols

Transport hazard class(es):

2.1 Gases Class

Marine pollutant: No

Symbol (fish and tree) Special precautions for user: Warning: Gases

F-D,S-Ŭ **EMS Number:**

Packaging Group: UN "Model Regulation": UN1950, Aerosols, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

1330-20-7 xylene (mix)

7779-90-0 zinc phosphate

1314-13-2 zinc oxide

Toxic Substances Control Act

All hazardous ingredients are found on the inventory list of substances. (TSCA):

(Contd. on page 5)

D, I, II

D, I, II

Safety Data Sheet

Printing date 01/09/2023 Revised On 01/09/2023

Trade name: GREEN ZINC PHOSPHATE (Contd. of page 4) **Canadian Domestic Substances List** (DSL): Consumer Product Safety Comission (CPSC): All ingredients are listed or exempted. This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead. California Proposition 65 chemicals known to cause cancer: 100-41-4 ethyl benzene 1333-86-4 Carbon black 108-10-1 methyl isobutyl ketone Prop 65 chemicals known to cause birth defects or reproductive harm: 67-56-1 methanol 108-10-1 methyl isobutyl ketone EPA: 110-19-0 Isobutyl Acetate D 1330-20-7 xylene (mix)

16 Other information Contact: Regulatory Affairs

7779-90-0 zinc phosphate

67-64-1 Acetone 1314-13-2 zinc oxide