



Printing date 03/06/2019 Reviewed on 10/19/2018

# 1 Identification

#### - Product identifier

Trade name: Vibra-TITE® Excel CA Accelerator

- Synonyms: 621 Excel CA Accelerator

- Part number: VT621

- Application of the substance / the mixture Accelerator

# - Details of the supplier of the safety data sheet

- Manufacturer/Supplier:

ND Industries, Inc 1000 North Crooks Road Clawson, MI 48017

USA

Telephone: +1-248-288-0000 Email: info@ndindustries.com Website: www.ndindustries.com

- Information department: Product safety department

- Emergency telephone number:

United States: 1-800-424-9300 International: +1-703-527-3887

# 2 Hazard(s) identification

# - Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

# - Label elements

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

- Hazard pictograms







GHS02 GHS07 GHS08

- Signal word Danger

#### - Hazard-determining components of labeling:

heptane acetone

#### - Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

# - Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

# Safety Data Sheet

Printing date 03/06/2019 Reviewed on 10/19/2018

#### Trade name: Vibra-TITE® Excel CA Accelerator

(Contd. of page 1) P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/lighting/equipment. P242 Use only non-sparking tools. P261 Avoid breathing dust/fume/gas/mist/vapors/spray P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/protective clothing/eye protection/face protection. P280 Wear protective gloves. P280 Wear eye protection / face protection. P301+P310 If swallowed: Immediately call a poison center/doctor. P321 Specific treatment (see on this label). P331 Do NOT induce vomiting. P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 Call a poison center/doctor if you feel unwell. P362+P364 Take off contaminated clothing and wash it before reuse. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P403+P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

#### - Classification system:

P501

- NFPA ratings (scale 0 - 4)



Health = 2 Fire = 3 Reactivity = 0

# - HMIS-ratings (scale 0 - 4)



### - Other hazards

- Results of PBT and vPvB assessment
  - PBT: Not applicable.
  - vPvB: Not applicable.

# 3 Composition/information on ingredients

#### - Chemical characterization: Mixtures

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- Dangerous components:		
CAS: 67-64-1	acetone	60 – 69%
	Flam. Liq. 2, H225; Eye Irrit. 2A, H319; STOT SE 3, H336	
CAS: 142-82-5	heptane	30 – 39%
	Flam. Liq. 2, H225; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336	
CAS: 99-97-8	N,N-dimethyl-p-toluidine	≤ 1%
	Acute Tox. 3, H301; Acute Tox. 3, H311; Carc. 2, H351; STOT RE 2, H373; Flam. Liq. 4, H227	

# 4 First-aid measures

# Description of first aid measures

## - After inhalation:

In case of unconsciousness place patient stably in side position for transportation. Supply fresh air; consult doctor in case of complaints.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
  - Most important symptoms and effects, both acute and delayed No further relevant information available.
  - Indication of any immediate medical attention and special treatment needed No further relevant information available.

# 5 Fire-fighting measures

#### - Extinguishing media

- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. CO2, sand, extinguishing powder. Do not use water.

# Safety Data Sheet

Printing date 03/06/2019 Reviewed on 10/19/2018

Trade name: Vibra-TITE® Excel CA Accelerator

(Contd. of page 2)

- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
  - Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

# 6 Accidental release measures

# Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Wear protective clothing.

#### - Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

#### - Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Dispose of the collected material according to regulations.

#### - Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# 7 Handling and storage

#### - Handling:

#### - Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

## Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

# - Conditions for safe storage, including any incompatibilities

- Storage:
  - Requirements to be met by storerooms and receptacles: Store in a cool location.
  - Information about storage in one common storage facility: Not required.
  - Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Specific end use(s) No further relevant information available.

# 8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- Control parameters

# - Components with limit values that require monitoring at the workplace: CAS: 67-64-1 acetone PEL Long-term value: 2400 mg/m³, 1000 ppm REL Long-term value: 590 mg/m³, 250 ppm TLV Short-term value: 1187 mg/m³, 500 ppm

CAS: 142-82-5 heptane

PEL Long-term value: 2000 mg/m³, 500 ppm REL Long-term value: 350 mg/m³, 85 ppm

Ceiling limit value: 1800\* mg/m³, 440\* ppm

Long-term value: 594 mg/m<sup>3</sup>, 250 ppm

\*15-min

BEI

TLV Short-term value: 2050 mg/m³, 500 ppm Long-term value: 1640 mg/m³, 400 ppm

#### CAS: 99-97-8 N,N-dimethyl-p-toluidine

WEEL Long-term value: 0.5 ppm

Printing date 03/06/2019 Reviewed on 10/19/2018

Trade name: Vibra-TITE® Excel CA Accelerator

(Contd. of page 3)

#### Ingredients with biological limit values:

# CAS: 67-64-1 acetone

BEI 50 mg/L Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

- Additional information: The lists that were valid during the creation were used as basis.

#### Exposure controls

# - Personal protective equipment:

# - General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

#### - Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

# - Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

# - Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection:



Tightly sealed goggles

- Body protection: Protective work clothing

# 9 Physical and chemical properties

or nyologi and chomical proportion		
- Information on basic physical and chemical properties - General Information		
- Appearance:		
- Form:	Fluid	
- Color:	Amber colored	
- Odor:	Solvent-like	
- Odor threshold:	Not determined.	
- pH-value:	Not determined.	
<ul> <li>Change in condition</li> <li>Melting point/Melting range:</li> <li>Boiling point/Boiling range:</li> </ul>	Undetermined. ≥ 55.8 – ≤ 56.6 °C (≥ 132.4 – ≤ 133.9 °F)	
- Flash point:	-17 °C (1.4 °F)	
- Flammability (solid, gaseous):	Not applicable.	
- Ignition temperature:	215 °C (419 °F)	
<ul> <li>Decomposition temperature:</li> </ul>	Not determined.	
- Auto igniting:	Product is not selfigniting.	
- Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.	
- Explosion limits:		
- Lower:	1.1 Vol %	
	(Contd. on none E)	

Printing date 03/06/2019 Reviewed on 10/19/2018

Trade name: Vibra-TITE® Excel CA Accelerator

(Contd. of page 4)

- Upper:	13 Vol %	
- Vapor pressure at 20 °C (68 °F):	≤ 233 hPa (≤ 174.8 mm Hg)	
- Density at 20 °C (68 °F):	~ 0.75262 g/cm³ (~ 6.28061 lbs/gal)	
Relative density	Not determined.	
· Vapor density	Not determined.	
- Evaporation rate	Not determined.	
- Solubility in / Miscibility with		
- Water:	Not miscible or difficult to mix.	
- Partition coefficient (n-octanol/water): Not determined.		
- Viscosity:		
- Dynamic:	Not determined.	
- Kinematic:	Not determined.	
- Solvent content:		
<ul> <li>Organic solvents:</li> </ul>	99.6 %	
- VOC content:	34.50 %	
	~ 259.7 g/l / ~ 2.17 lb/gal	
- Solids content:	0.0 %	
- Other information	No further relevant information available.	

# 10 Stability and reactivity

- Reactivity No further relevant information available.
  - Chemical stability
    - Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

# 11 Toxicological information

- Information on toxicological effects
  - Acute toxicity:

-	LD/LC50 values that are relevant for classification:	
ATE (Ad	ATE (Acute Toxicity Estimate)	
Oral	LD50 26,316 mg/kg	
Dermal	LD50 78,947 mg/kg	
CAS: 67-64-1 acetone		
Oral	LD50   5,800 mg/kg (rat)	
Dermal	LD50 20,000 mg/kg (rabbit)	
CAS: 99-97-8 N,N-dimethyl-p-toluidine		
Oral	LD50   100 mg/kg (ATE)	
Dermal	LD50 300 mg/kg (ATE)	
	Drimony irritant affacts	

- Primary irritant effect:
  - on the skin: Irritant to skin and mucous membranes.
  - on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

- Carcinogenic categories

- IARC (International Agency for Research on Cancer)	
CAS: 99-97-8 N,N-dimethyl-p-toluidine	2B
- NTP (National Toxicology Program)	
None of the ingredients is listed.	
- OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

Printing date 03/06/2019 Reviewed on 10/19/2018

Trade name: Vibra-TITE® Excel CA Accelerator

(Contd. of page 5)

# 12 Ecological information

- Toxicity
  - **Aquatic toxicity:** No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
  - Bioaccumulative potential No further relevant information available.
  - Mobility in soil No further relevant information available.
- Ecotoxical effects:
  - Remark: Very toxic for fish
- Additional ecological information:
  - General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

- Results of PBT and vPvB assessment
  - **PBT:** Not applicable.
  - vPvB: Not applicable.
- Other adverse effects No further relevant information available.

# 13 Disposal considerations

- Waste treatment methods
  - Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:
  - **Recommendation:** Disposal must be made according to official regulations.

# 14 Transport information

14 Transport information	
- UN-Number - DOT, IMDG, IATA	UN1993
- UN proper shipping name - DOT - IMDG	Flammable liquids, n.o.s. (Acetone, Heptanes) FLAMMABLE LIQUID, N.O.S. (ACETONE, HEPTANES),
- IATA	MARINE POLLUTANT FLAMMABLE LIQUID, N.O.S. (ACETONE, HEPTANES)
- Transport hazard class(es)	
- DOT	
NAME OF THE PROPERTY OF THE PR	
- Class - Label	3 Flammable liquids 3
- IMDG	
¥2	
- Class	3 Flammable liquids
- Label	3
- IATA	
- Class - Label	3 Flammable liquids 3
- Packing group - DOT, IMDG, IATA	II

Printing date 03/06/2019 Reviewed on 10/19/2018

Trade name: Vibra-TITE® Excel CA Accelerator

(Contd. of page 6) - Environmental hazards: Product contains environmentally hazardous substances: heptane - Marine pollutant: Symbol (fish and tree) - Special precautions for user Warning: Flammable liquids - Danger code (Kemler): 33 - EMS Number: F-E,<u>S-E</u> - Stowage Category R Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. - Transport/Additional information: - DOT Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L - IMDG - Limited quantities (LQ) 1L - Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml - UN "Model Regulation": UN 1993 FLAMMABLE LIQUID, N.O.S. (ACETONE, HEPTANES),

3, II, ENVIRONMENTALLY HAZARDOUS

# 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture - Sara

- Section 355 (extremely hazardous substances):
None of the ingredients is listed.
- Section 313 (Specific toxic chemical listings):
None of the ingredients is listed.
- TSCA (Toxic Substances Control Act):
All ingredients are listed.
- Hazardous Air Pollutants
None of the ingredients is listed.
- Proposition 65
- Chemicals known to cause cancer:
CAS: 99-97-8 N,N-dimethyl-p-toluidine
- Chemicals known to cause reproductive toxicity for females:

CAS: 99-97-8 N,N-dimethyl-p-toluidine

- Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

- Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

- Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- Carcinogenic categories

- <b>EP</b>	A (Environmental Protection Agency)	
CAS: 67-64-1	acetone	
CAS: 142-82-5	heptane	D
- TL	V (Threshold Limit Value established by ACGIH)	
CAS: 67-64-1	acetone	A4
- NIC	OSH-Ca (National Institute for Occupational Safety and Health)	
None of the ing	redients is listed.	
- Chemical sa	fety assessment: A Chemical Safety Assessment has not been carried out	

- Unemical satety assessment: A Chemical Satety Assessment has not been carried out.

# 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: ND Industries, Inc. - Safety, Health and Environmental Affaires

Printing date 03/06/2019 Reviewed on 10/19/2018

### Trade name: Vibra-TITE® Excel CA Accelerator

(Contd. of page 7)

- Contact: Safety, Health and Environmental Affaires

Date of preparation / last revision 03/06/2019 / 16

- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation

IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists

ELINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

BEI: Biological Exposure Limit Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 4: Flammable liquids – Category 4

Acute Tox. 3: Acute toxicity – Category 3
Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Carc. 2: Carcinogenicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1

# - \* Data compared to the previous version altered.

The information set forth is based on information that ND Industries, Incorporated believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and ND Industries Inc. assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

®ND and ND Industries, Inc. are registered trademarks of ND Industries Incorporated, ®Vibra-TITE is a registered trademark of ND Industries, Inc.