

Safety Data Sheet
Slide Out

SECTION I - IDENTIFICATION

PRODUCT IDENTIFIER: Slide Out
PRODUCT CODE: 5380
RECOMMENDED USE: Dry Silicone Spray
RESTRICTIONS ON USE: None Known
COMPANY NAME: QuestSpecialty Corporation
COMPANY ADDRESS: PO Box 624 Brenham, TX 77834
COMPANY PHONE: 1-800-231-0454
EMERGENCY PHONE: 800-255-3924

SECTION II – HAZARDS IDENTIFICATION

CLASSIFICATION: Flammable Aerosol: Category 1
Liquefied Gas
Skin Irritant: Category 2
Eye Irritant: Category 2A
Specific Target Organ Toxicity (Single Exposure): Category 3
Aspiration Hazard: Category 1

HAZARD STATEMENT(S): DANGER: Extremely Flammable Aerosol. Contains gas under pressure: May explode if heated. Causes skin and serious eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

This product contains the following percentage of chemicals of unknown toxicity: 0%

PRECAUTIONARY STATEMENTS: Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Avoid breathing fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state, and national regulations.

SYMBOL:



HAZARDS NOT OTHERWISE CLASSIFIED: N/A

SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Acetone	67-64-1	30-60%
Heptane	142-82-5	10-30%
Propane/n-Butane	68476-86-8	30-60%

SECTION IV - FIRST AID MEASURES

EYES: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

INGESTION: If swallowed: Rinse mouth. Do NOT induce vomiting. Get medical advice or attention.

INHALATION: If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell.

SKIN: Immediately wash with soap and water for 15 minutes. Remove contaminated clothing and shoes immediately. Seek medical attention if irritation develops.

ACUTE HEALTH HAZARDS: Eyes: redness, tearing, blurred vision

Safety Data Sheet

Slide Out

Skin: defatting and dermatitis

Inhalation: drowsiness and dizziness

Oral: abdominal irritation, nausea, vomiting, and diarrhea

CHRONIC HEALTH HAZARDS: None known

NOTE TO PHYSICIAN: If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

SECTION V – FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: CO₂, Dry Chemical

UNSUITABLE EXTINGUISHING MEDIA: Water spray/stream.

SPECIAL FIRE FIGHTING PROCEDURES: Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Avoid breathing smoke, fumes, and decomposition products. Cool fire exposed containers with water fog to prevent bursting.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep away from sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon

SECTION VI – ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

SPILL: Eliminate all sources of ignition. absorb liquid with non-combustible material like vermiculite, sand or earth and clean up with mop or rag.

WASTE DISPOSAL: Dispose of contents in accordance with federal, state, and local regulations. Do not dump in sewers. Wrap container and place in trash collection, do not puncture, incinerate, or reuse container.

RCRA STATUS: Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION VII – HANDLING AND STORAGE

HANDLING AND STORAGE: Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Pressurized container: Do not pierce or burn, even after use. Store locked up.

OTHER PRECAUTIONS: Keep out of the reach of children.

INCOMPATIBILITY: Strong alkalis, oxidizers, bases, reactive metals, and natural rubber

SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Acetone	1000 ppm	500 ppm
Heptane	500 ppm	400 ppm
Propane/n-Butane	1000 ppm	1000 ppm

ENGINEERING CONTROLS / VENTILATION: Use only outdoors or in a well-ventilated area.

RESPIRATORY PROTECTION: Wear NIOSH/MSHA approved organic vapor respiratory protection if listed exposure limits (section VIII) are exceeded.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses and chemical resistant gloves

ADDITIONAL MEASURES: Wash hands thoroughly after handling.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Clear, Colorless Spray

ODOR: Solvent odor

ODOR THRESHOLD: N/D

pH: N/A

MELTING POINT/FREEZING POINT: N/D

INITIAL BOILING POINT AND BOILING RANGE: <200°F

FLASH POINT: <5° F

EVAPORATION RATE: >3 Fast

Safety Data Sheet

Slide Out

FLAMMABILITY(solid/gas): Extremely Flammable Aerosol

UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:

LOWER FLAMMABILITY LIMIT: N/D

UPPER FLAMMABILITY LIMIT: N/D

EXPLOSIVE LIMIT LOWER (%): N/D

EXPLOSIVE LIMIT UPPER (%): N/D

VAPOR PRESSURE (mm Hg): >36 @ 77°F (25°C)

VAPOR DENSITY (AIR=1): 4.5

RELATIVE DENSITY (H₂O=1): 0.74 - 0.77

SOLUBILITY(IES): 0%

PARTITION COEFFICIENT: n-OCTANOL/WATER (K_{ow}): N/D

AUTOIGNITION TEMPERATURE: N/D

DECOMPOSITION TEMPERATURE: N/D

VISCOSITY: N/D

SECTION X – STABILITY AND REACTIVITY

REACTIVITY: Certain plastics, rubber, strong oxidizers

CHEMICAL STABILITY: Stable

POSSIBLE HAZARDOUS REACTIONS: None Known

CONDITIONS TO AVOID: Temperatures greater than 122°F and sources of ignition.

INCOMPATIBLE MATERIALS: Strong alkalis, oxidizers, bases, reactive metals, and natural rubber

HAZARDOUS DECOMPOSITION PRODUCTS: Silicone Dioxide, Carbon oxides, Formaldehyde

SECTION XI – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: Acetone (67-64-1) LD₅₀ (Oral, Rat) 5800 mg/kg; LD₅₀ (Oral, Mouse) 3000 mg/kg; LD₅₀ (Oral, Rabbit) 5340 mg/kg; LC₅₀ (Inhalation, Rat, 8hr) 50100 mg/m³; LC₅₀ (Inhalation, Mouse, 4hr) 44,000 mg/m³ Heptane (142-82-5) LC₅₀ (Vapors, Mice) 1600 ppm

ROUTES OF ENTRY: Eyes, Ingestion, Inhalation, Skin

EYES: Causes irritation, redness, tearing, pain, blurred vision.

INGESTION: Not a likely route of exposure under normal product handling conditions. May cause gastrointestinal irritation, nausea, diarrhea, vomiting.

INHALATION: Causes dizziness, excessive or prolonged exposure may cause unconsciousness.

SKIN: Causes localized defatting, irritation, dermatitis.

MEDICAL CONDITION AGGRAVATED: Excessive exposure will aggravate pre-existing skin disorders, respiratory, liver, kidney, cardiovascular or pulmonary illnesses.

ACUTE HEALTH HAZARDS: Eyes: redness, tearing, blurred vision

Skin: defatting and dermatitis

Inhalation: drowsiness and dizziness

Oral: abdominal irritation, nausea, vomiting, and diarrhea

CHRONIC HEALTH HAZARDS: None known

CARCINOGENICITY: OSHA: No ACGIH: N/A NTP: No IARC: N/A OTHER: N/A

SECTION XII – ECOLOGICAL INFORMATION

ECOTOXICITY: Acetone (67-64-1) LC₅₀ (Trout, 96hr) 5540 mg/L; LC₅₀ (Bluegill, 96hr) 8300 mg/L; LC₅₀ (Fathead Minnow, 96hr) 7500 mg/L

PERSISTENCE AND DEGRADABILITY: Component or components of this product are not biodegradable.

BIOACCUMULATIVE POTENTIAL: This product is not expected to bioaccumulate.

MOBILITY IN SOIL: This product is mobile in soil.

OTHER ADVERSE EFFECTS: This material is toxic to aquatic life.

SECTION XIII – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of contents in accordance with federal, state, and local regulations. Do not dump in sewers. Wrap container and place in trash collection, do not puncture, incinerate, or reuse container.

RCRA STATUS: Waste likely considered D001 (Ignitable waste), under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

Safety Data Sheet
Slide Out

SECTION XIV - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Aerosols
HAZARD CLASS/DIVISION: 2.1
UN/NA NUMBER: UN 1950
PACKING GROUP: N/A

AIR SHIPMENT

PROPER SHIPPING NAME: Aerosols, flammable
HAZARD CLASS/DIVISION: 2.1
UN/NA NUMBER: UN 1950
PACKING GROUP: N/A

SHIPPING BY WATER:

VESSEL (IMO/IMDG)
PROPER SHIPPING NAME: Aerosols, Ltd. Qty.
HAZARD CLASS/DIVISION: 2.1
UN/NA NUMBER: UN 1950
PACKING GROUP: N/A
ENVIRONMENTAL HAZARDS WATER: Marine Pollutant

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: All Chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): Acetone (67-64-1) Reportable Quantity = 5,000 lbs

SARA 311/312 HAZARD CATEGORIES: Acute Health, Fire

SARA 313 REPORTABLE INGREDIENTS: None

STATE REGULATIONS: Acetone (67-64-1) Connecticut hazardous material survey, Illinois toxic substances disclosure to employee act, Illinois chemical safety act, New York release reporting list, **RTK** - RI, PA, FL, MN, MA, NJ; Massachusetts spill list, New Jersey spill list, Louisiana spill reporting, California List of Hazardous Substances (8 CCR 339): Acetone TSCA 8(b) inventory: Acetone TSCA 4(a) final test rules: Acetone TSCA 8(a) IUR: Acetone

Heptane (142-82-5) California Director's List of Hazardous Substances, Connecticut hazardous material survey, Illinois toxic substances disclosure to employee act, New Jersey RTK, Massachusetts RTK, Minnesota RTK, Pennsylvania RTK, Rhode Island RTK

INTERNATIONAL REGULATIONS: All components are listed or exempted.

NFPA HEALTH:	1	HMIS HEALTH:	1
NFPA FLAMMABILITY:	3	HMIS FLAMMABILITY:	3
NFPA REACTIVITY:	0	HMIS REACTIVITY:	0
NFPA OTHER:	None	HMIS PROTECTION:	B

SECTION XVI - OTHER INFORMATION

PREPARATION BY: Andrew Bach

DATE PREPARED: 05/10/2013

REVISION DATE: 02/28/2019

N/A = Not Applicable; N/D = Not Determined

DISCLAIMER: To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations

Safety Data Sheet

Slide Out

regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.