

Version	Revision Date:	SDS Number:	Date of last issue: 09/06/2018
2.1	03/29/2023	60000001477	Date of first issue: 07/05/2018

SECTION 1. IDENTIFICATION

Product name Product code	:	PRIMEGUARD CARB CLNR AERO 12/10OZ CB16			
Manufacturer or supplier's	deta	ails			
Company name of supplier Address	:				
Email Address Telephone Emergency telephone num- ber	:	EHS@niteoproducts.com 1-844-696-4836 1-800-424-9300 / 1-703-741-5970			
Recommended use of the chemical and restrictions on use					

Recommended use	:	BRAKE PARTS CLEANER
Restrictions on use	:	Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

, Flammable aerosols	:	Category 1
Acute toxicity (Oral)	:	Category 3
Acute toxicity (Inhalation)	:	Category 3
Acute toxicity (Dermal)	:	Category 3
Skin irritation	:	Category 2
Eye irritation	:	Category 2A
Reproductive toxicity	:	Category 2
Specific target organ toxicity - single exposure	:	Category 1 (Central nervous system, Eyes)
Specific target organ toxicity - single exposure	:	Category 3 (Central nervous system)
Specific target organ toxicity - repeated exposure (Inhala- tion)	:	Category 2 (Neurologic: other (neuropsychological effects, audi- tory dysfunction and effects on color vision))
Aspiration hazard	:	Category 1

GHS label elements



Version 2.1	Revision Date: 03/29/2023	SDS Number: 600000001477	Date of last issue: 09/06/2018 Date of first issue: 07/05/2018
Haza	rd pictograms		
Signa	I word	: Danger	
Haza	rd statements	Toxic if swallo May be fatal if Causes skin ir Causes seriou May cause dro Suspected of Causes dama May cause da logical effects	nmable aerosol. wed, in contact with skin or if inhaled. swallowed and enters airways. ritation. is eye irritation. owsiness or dizziness. damaging the unborn child. ge to organs (Central nervous system, Eyes). mage to organs (Neurologic: other (neuropsycho- auditory dysfunction and effects on color vision)) nged or repeated exposure if inhaled.
Preca	autionary statements	Do not handle understood. Keep away fro smoking. Do not spray o Pressurized o Do not breath Wash skin tho Do not eat, dri Use only outdo	I instructions before use. until all safety precautions have been read and om heat/ sparks/ open flames/ hot surfaces. No on an open flame or other ignition source. ontainer: Do not pierce or burn, even after use. e dust/ fume/ gas/ mist/ vapours/ spray. roughly after handling. nk or smoke when using this product. oors or in a well-ventilated area. /e gloves/ protective clothing/ eye protection/ face
		Rinse mouth. IF ON SKIN: V CENTER/ doc IF INHALED: I for breathing. IF IN EYES: R Remove conta rinsing. IF exposed: C Do NOT induc If skin irritation If eye irritation	ED: Immediately call a POISON CENTER/ docto Vash with plenty of water. Call a POISON tor if you feel unwell. Remove person to fresh air and keep comfortable Call a POISON CENTER/ doctor. Rinse cautiously with water for several minutes. act lenses, if present and easy to do. Continue all a POISON CENTER or doctor/ physician. e vomiting. n occurs: Get medical advice/ attention. persists: Get medical advice/ attention. uminated clothing and wash before reuse.
		Storage: Store in a well Store locked u	-ventilated place. Keep container tightly closed. ip. unlight. Do not expose to temperatures exceedin



Version	Revision Date:	SDS Number:	Date of last issue: 09/06/2018
2.1	03/29/2023	60000001477	Date of first issue: 07/05/2018

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

CAS-No.	Concentration (% w/w)
67-56-1	>= 30 - < 50
108-88-3	>= 30 - < 50
67-64-1	>= 20 - < 30
124-38-9	>= 1 - < 5
	67-56-1 108-88-3 67-64-1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later. Do not leave the victim unattended.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice.
In case of skin contact	:	If symptoms persist, call a physician. If on clothes, remove clothes. Call a physician or poison control centre immediately. Remove contaminated clothing. If irritation develops, get med- ical attention. If on skin, rinse well with water. Wash contaminated clothing before re-use. If skin irritation persists, call a physician.
In case of eye contact	:	
If swallowed	:	Get medical attention immediately. Do NOT induce vomiting. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
Most important symptoms and effects, both acute and delayed	:	If symptoms persist, call a physician. Toxic if swallowed, in contact with skin or if inhaled. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness.



Version	Revision Date:	SDS Number:	Date of last issue: 09/06/2018
2.1	03/29/2023	600000001477	Date of first issue: 07/05/2018
		Causes damage May cause dama exposure if inhale This product con and central nerve lized to formic ac cause metabolic Since metabolisr onset may be de Ethanol compete been used to pre istration is indica anol concentratio removed by hem This material (or	age to organs through prolonged or repeated ed. tains methanol which can cause intoxication bus system depression. Methanol is metabo- id and formaldehyde. These metabolites can acidosis, visual disturbances and blindness. In is required for these toxic symptoms, their layed from 6 to 30 hours following ingestion. Is for the same metabolic pathway and has event methanol metabolism. Ethanol admin- ted in symptomatic patients or at blood meth- ons above 20 ug/dl. Methanol is effectively

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Water spray Carbon dioxide (CO2) Dry chemical Alcohol-resistant foam
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during fire- fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion prod- ucts	:	Carbon oxides
Specific extinguishing meth- ods	:	Product is compatible with standard fire-fighting agents.
Further information	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer- gency procedures	Use personal protective equipment. Remove all sources of ignition. Ensure adequate ventilation. Avoid breathing dust. Beware of vapours accumulating to form explosive concentra- tions. Vapours can accumulate in low areas. Evacuate personnel to safe areas. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Environmental precautions :	Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system.



Version	Revision Date:	SDS Number:	Date of last issue: 09/06/2018	
2.1	03/29/2023	600000001477	Date of first issue: 07/05/2018	

If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition. Use only explosion-proof equipment. Do not spray on a naked flame or any incandescent material.
Advice on safe handling	:	Open drum carefully as content may be under pressure. Provide sufficient air exchange and/or exhaust in work rooms. Do not breathe vapours/dust. Do not smoke. Take precautionary measures against static discharges. Avoid contact with skin and eyes.
		Dispose of rinse water in accordance with local and national regulations. Container hazardous when empty. Smoking, eating and drinking should be prohibited in the ap- plication area. For personal protection see section 8.
Conditions for safe storage	:	BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and
		kept upright to prevent leakage. Observe label precautions. No smoking.
Further information on stor- age stability	:	No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 260 mg/m3	NIOSH REL
		ST	250 ppm 325 mg/m3	NIOSH REL
		TWA	200 ppm 260 mg/m3	OSHA Z-1
		STEL	250 ppm 325 mg/m3	OSHA P0
		TWA	200 ppm	OSHA P0



rsion	Revision Date: 03/29/2023	SDS Number: 600000001477		last issue: 09/06/2018 first issue: 07/05/2018	
I		I	1	260 mg/m3	1
Tolue	222	108-88-3	TWA	200 mg/ms 20 ppm	ACGIH
Tolue	lie	100-00-3	TWA		NIOSH RE
			IWA	100 ppm 375 mg/m3	
			ST	150 ppm	NIOSH RE
			01	560 mg/m3	
			TWA	200 ppm	OSHA Z-2
			CEIL	300 ppm	OSHA Z-2
			Peak	500 ppm (10 minutes)	OSHA Z-2
			TWA	100 ppm 375 mg/m3	OSHA P0
			STEL	150 ppm 560 mg/m3	OSHA P0
Aceto	one	67-64-1	TWA	250 ppm	ACGIH
			STEL	500 ppm	ACGIH
			TWA	250 ppm 590 mg/m3	NIOSH RE
			TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
			TWA	750 ppm 1,800 mg/m3	OSHA P0
			STEL	1,000 ppm 2,400 mg/m3	OSHA P0
Carbo	on dioxide	124-38-9	TWA	5,000 ppm	ACGIH
			STEL	30,000 ppm	ACGIH
			TWA	5,000 ppm 9,000 mg/m3	NIOSH RE
			ST	30,000 ppm 54,000 mg/m3	NIOSH RE
			TWA	5,000 ppm 9,000 mg/m3	OSHA Z-1
			TWA	10,000 ppm 18,000 mg/m3	OSHA P0
			STEL	30,000 ppm 54,000 mg/m3	OSHA P0

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentra- tion	Basis
Methanol	67-56-1	Methanol	Urine	End of shift (As soon as possible after exposure ceases)	15 mg/l	ACGIH BEI
Toluene	108-88-3	Toluene	In blood	Prior to last shift of work- week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as	0.03 mg/l	ACGIH BEI



ersion Revision Date: 1 03/29/2023			Number: 00001477	Date of last issue: 09/06/2018 Date of first issue: 07/05/2018			
					possible after exposure ceases)		
			o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI
Aceto	one	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
-	neering measures	v a a	rovide sufficien entilation to ma pplicable) or be pparent advers	aintain expo elow levels t	sure below ex	kposure guide	elines (if
	onal protective equ iratory protection	: Ir p Ir	n the case of va roved filter. In the case of de			-	
Hand	protection	d	pproved filter.				
	emarks	e c g	Vear resistant of r). The suitabil ussed with the loves that show	ity for a spe producers o v tears, pinh	cific workplac of the protecti noles, or signs	e should be c ve gloves. Dis s of wear.	lis- scard
Eye p	protection		/ear chemical xposure of the				ntial for
Skin a	and body protection	c V Ir F S	hoose body pr entration of the Vear as approp npervious cloth lame-resistant afety shoes temove and wa	e dangerous riate: ning clothing	substance at	the work pla	ce.
Hygie	ene measures	: H P A V V	landle in accor ractice. void contact w /hen using do /ash hands be ne product. /hen using do	dance with g ith skin, eye not smoke. fore breaks	good industria es and clothin and immedia	al hygiene and g.	d safety

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	aerosol
Melting point/freezing point	:	No data available



Vers 2.1	sion	Revision Date: 03/29/2023		S Number: 0000001477	Date of last issue: 09/06/2018 Date of first issue: 07/05/2018
	Boiling Flash p	point/boiling range oint	:	No data available -20 °C Method: closed o Value for Compo	up
	Evapor	ation rate	:	No data available	
		explosion limit / Upper bility limit	:	No data available	
		explosion limit / Lower bility limit	:	No data available	
	Vapour	pressure	:	No data available	9
	Density	1	:	No data available)
	Solubili Wat	ity(ies) er solubility	:	No data available	3
	Viscosi Visc	ty cosity, kinematic	:	No data available	9
	VOC %	By Weight	:	66 %	

SECTION 10. STABILITY AND REACTIVITY

Reactivity Chemical stability Possibility of hazardous reac- tions	:	No decomposition if stored and applied as directed. No decomposition if stored and applied as directed. No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid Incompatible materials Hazardous decomposition products	:	Heat, flames and sparks. Strong oxidizing agents Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Information on like	ly routes of exposure
---------------------	-----------------------

Inhalation Eye contact Skin contact Ingestion

Acute toxicity

Toxic if swallowed, in contact with skin or if inhaled.

Product:

Acute oral toxicity	:	Acute toxicity estimate: 299.39 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: 8.06 mg/l Exposure time: 4 h Test atmosphere: vapour



Version 2.1	Revision Date: 03/29/2023		05 Number: 0000001477	Date of last issue: 09/06/2018 Date of first issue: 07/05/2018
			Method: Calculati	on method
Acute	e dermal toxicity	:	Acute toxicity esti Method: Calculati	mate: 898.16 mg/kg on method
<u>Com</u>	ponents:			
Meth	anol:			
Acute	e oral toxicity	:	LDLo (Humans): Assessment: The gestion.	300 mg/kg component/mixture is toxic after single in-
Acute	e inhalation toxicity	:	Test atmosphere: Assessment: The inhalation.	dust/mist component/mixture is toxic after short term
Acute	e dermal toxicity	:	LD50 (Rabbit): 12 Assessment: The tact with skin.	2,800 mg/kg component/mixture is toxic after single con-
Tolu	ene:			
Acute	e oral toxicity	:	LD50 (Rat): > 5,0	00 mg/kg
Acute	e inhalation toxicity	:	LC50 (Rat, males Exposure time: 4 Test atmosphere:	h
Acute	e dermal toxicity	:	LD50 (Rabbit): 12	2,124 mg/kg
Acet	one:			
	e oral toxicity	:	LD50 (Rat, femal	e): 5,800 mg/kg
Acute	e inhalation toxicity	:	LC50 (Rat, female Exposure time: 4 Test atmosphere:	ĥ
Acute	e dermal toxicity	:	LD50 (Rabbit): >	7,426 mg/kg
	corrosion/irritation			
Prod	uct:			

<u>Product:</u> Remarks: May cause skin irritation and/or dermatitis.

Components:

Methanol:

Species: Rabbit Result: No skin irritation

Toluene: Result: Irritating to skin.



Version	Revision Date:	SDS Number:
2.1	03/29/2023	60000001477

Date of last issue: 09/06/2018 Date of first issue: 07/05/2018

Acetone:

Result: Possibly irritating to skin

Result: Repeated exposure may cause skin dryness or cracking.

Carbon dioxide:

Assessment: No skin irritation Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

Methanol: Species: Rabbit Result: Possibly irritating to eyes

Toluene: Result: Irritating to eyes.

Acetone:

Result: Irritating to eyes. Assessment: Irritating to eyes.

Carbon dioxide: Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Methanol:

Test Type: Maximisation Test Species: Guinea pig Assessment: Does not cause skin sensitisation. Method: OECD Test Guideline 406

Toluene:

Species: Guinea pig Method: Directive 67/548/EEC, Annex V, B.6.



				Date of last issue: 09/06/2018 Date of first issue: 07/05/2018
--	--	--	--	---

Result: Not a skin sensitizer.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.					
IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.				
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.				
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.				

Reproductive toxicity

Suspected of damaging the unborn child.

Components:

Toluene:

Reproductive toxicity - As-	:	Some evidence of adverse effects on development, based on
sessment		animal experiments.

STOT - single exposure

May cause drowsiness or dizziness. Causes damage to organs (Central nervous system, Eyes).

Components:

Methanol:

Target Organs: Central nervous system, Eyes Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 1.

Toluene:

Exposure routes: Inhalation Target Organs: Central nervous system Assessment: May cause drowsiness or dizziness.

Acetone:

Exposure routes: Inhalation Target Organs: Nervous system Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

May cause damage to organs (Neurologic: other (neuropsychological effects, auditory dysfunction and effects on color vision)) through prolonged or repeated exposure if inhaled.



Version	Revision Date:	SDS Number:
2.1	03/29/2023	60000001477

Date of last issue: 09/06/2018 Date of first issue: 07/05/2018

Components:

Toluene:

Exposure routes: Inhalation

Target Organs: Neurologic: other (neuropsychological effects, auditory dysfunction and effects on color vision)

Assessment: May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

Toluene:

May be fatal if swallowed and enters airways.

Acetone:

May be harmful if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

Additional ecological information	:	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
		Toxic to aquatic life.
		Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	: Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR UN/ID No.

: UN 1950



Version 2.1	Revision Date: 03/29/2023		DS Number: 00000001477	Date of last issue: 09/06/2018 Date of first issue: 07/05/2018
Proper shipping name Class Packing group Labels Packing instruction (cargo aircraft) Packing instruction (passenger aircraft)		:	Aerosols, flamm 2.1 Not assigned by 2.1 203 203	
IMDG-Code UN number Proper shipping name Class Packing group Labels EmS Code Marine pollutant		:	UN 1950 AEROSOLS 2.1 Not assigned by 2.1 F-D, S-U no	regulation

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR		
UN/ID/NA number	:	UN 1950
Proper shipping name	:	Aerosols
Class	:	2.1
Packing group	:	Not assigned by regulation
Labels	:	2.1
ERG Code	:	126
Marine pollutant	:	no

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Xylene	1330-20-7	100	100 (F003)
Xylene	1330-20-7	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.




Version 2.1	Revision Date: 03/29/2023	SDS Number: 600000001477		
SARA 313			omponents are subject to re RA Title III, Section 313:	porting levels es-
		Methanol	67-56-1	>= 30 - < 50 %
		Toluene	108-88-3	>= 30 - < 50 %

California Prop. 65

WARNING: This product can expose you to chemicals including Benzene, Ethylbenzene, which is/are known to the State of California to cause cancer, and Methanol, Toluene, Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION





Revision Date : 03/29/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN