



Version Revision Date: SDS Number: Date of last issue: 09/06/2018 2.1 03/29/2023 600000001477 Date of first issue: 07/05/2018

SECTION 1. IDENTIFICATION

Product name : PRIMEGUARD CARB CLNR AERO 12/16.25OZ

Product code : CB20

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC Address : Dallas TX 75225

Email Address : EHS@niteoproducts.com

Telephone : 1-844-696-4836

Emergency telephone num- : 1-800-424-9300 / 1-703-741-5970

ber

Recommended use of the chemical and restrictions on use

Recommended use : BRAKE PARTS CLEANER

Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable aerosols : Category 1

Acute toxicity (Oral) : Category 3

Acute toxicity (Inhalation) : Category 3

Acute toxicity (Dermal) : Category 3

Skin irritation : Category 2

Eye irritation : Category 2A

Reproductive toxicity : Category 2

Specific target organ toxicity

- single exposure

Category 1 (Central nervous system, Eyes)

Specific target organ toxicity

- single exposure

: Category 3 (Central nervous system)

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

Category 2 (Neurologic: other (neuropsychological effects, audi-

tory dysfunction and effects on color vision))

Aspiration hazard : Category 1

GHS label elements

PRIMEGUARD® CARB CLEANER



Version Date of last issue: 09/06/2018 Revision Date: SDS Number: 2.1 03/29/2023 60000001477 Date of first issue: 07/05/2018

Hazard pictograms









Signal word Danger

Hazard statements Extremely flammable aerosol.

> Toxic if swallowed, in contact with skin or if inhaled. May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging the unborn child.

Causes damage to organs (Central nervous system, Eyes). May cause damage to organs (Neurologic: other (neuropsychological effects, auditory dysfunction and effects on color vision))

through prolonged or repeated exposure if inhaled.

Precautionary statements

Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

Wash skin thoroughly after handling.

Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area.

Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

IF SWALLOWED: Immediately call a POISON CENTER/ doctor. Rinse mouth.

IF ON SKIN: Wash with plenty of water. Call a POISON

CENTER/ doctor if you feel unwell.

IF INHALED: Remove person to fresh air and keep comfortable

for breathing. Call a POISON CENTER/ doctor.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed: Call a POISON CENTER or doctor/ physician.

Do NOT induce vomiting.

If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

PRIMEGUARD® CARB CLEANER



Version Revision Date: Date of last issue: 09/06/2018 SDS Number: 03/29/2023 60000001477 Date of first issue: 07/05/2018 2.1

Disposal:

Dispose of contents/ container to an approved waste disposal

plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Methanol	67-56-1	>= 30 - < 50
Toluene	108-88-3	>= 30 - < 50
Acetone	67-64-1	>= 20 - < 30
Carbon dioxide	124-38-9	>= 1 - < 5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

Move out of dangerous area. General advice

Consult a physician.

Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled Move to fresh air.

Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

If on clothes, remove clothes. In case of skin contact

Call a physician or poison control centre immediately.

Remove contaminated clothing. If irritation develops, get med-

ical attention.

If on skin, rinse well with water.

Wash contaminated clothing before re-use. If skin irritation persists, call a physician.

Immediately flush eye(s) with plenty of water. In case of eye contact

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed Get medical attention immediately.

Do NOT induce vomiting. Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms

and effects, both acute and

delayed

Toxic if swallowed, in contact with skin or if inhaled. May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation. May cause drowsiness or dizziness.

PRIMEGUARD® CARB CLEANER



Version 2.1

Revision Date: 03/29/2023

SDS Number: 600000001477

Date of last issue: 09/06/2018 Date of first issue: 07/05/2018

Suspected of damaging the unborn child.

Causes damage to organs.

May cause damage to organs through prolonged or repeated

exposure if inhaled.

This product contains methanol which can cause intoxication and central nervous system depression. Methanol is metabolized to formic acid and formaldehyde. These metabolites can cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used to prevent methanol metabolism. Ethanol administration is indicated in symptomatic patients or at blood methanol concentrations above 20 ug/dl. Methanol is effectively removed by hemodialysis.

This material (or a component) has produced hyperglycemia

and ketosis following substantial ingestion.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray

Carbon dioxide (CO2)

Dry chemical

Alcohol-resistant foam High volume water jet

Unsuitable extinguishing

media

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod- :

ucts

Carbon oxides

Specific extinguishing meth-

ods

Product is compatible with standard fire-fighting agents.

Further information : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. Use a water spray to cool fully closed containers.

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment. Remove all sources of ignition.

Ensure adequate ventilation.

Avoid breathing dust.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Evacuate personnel to safe areas.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.

Do not flush into surface water or sanitary sewer system.





Version Revision Date: SDS Number: Date of last issue: 09/06/2018 2.1 03/29/2023 600000001477 Date of first issue: 07/05/2018

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Keep away from open flames, hot surfaces and sources of

ignition.

Use only explosion-proof equipment.

Do not spray on a naked flame or any incandescent material.

Advice on safe handling : Open drum carefully as content may be under pressure.

Provide sufficient air exchange and/or exhaust in work rooms.

Do not breathe vapours/dust.

Do not smoke.

Take precautionary measures against static discharges.

Avoid contact with skin and eyes.

Dispose of rinse water in accordance with local and national

regulations.

Container hazardous when empty.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

For personal protection see section 8.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Observe label precautions.

No smoking.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 260 mg/m3	NIOSH REL
		ST	250 ppm 325 mg/m3	NIOSH REL
		TWA	200 ppm 260 mg/m3	OSHA Z-1
		STEL	250 ppm 325 mg/m3	OSHA P0
		TWA	200 ppm	OSHA P0

PRIMEGUARD® CARB CLEANER



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/06/2018

 2.1
 03/29/2023
 600000001477
 Date of first issue: 07/05/2018

			260 mg/m3	
Toluene	108-88-3	TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m3	NIOSH REL
		ST	150 ppm 560 mg/m3	NIOSH REL
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm (10 minutes)	OSHA Z-2
		TWA	100 ppm 375 mg/m3	OSHA P0
		STEL	150 ppm 560 mg/m3	OSHA P0
Acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
Carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m3	NIOSH REL
		ST	30,000 ppm 54,000 mg/m3	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m3	OSHA Z-1
		TWA	10,000 ppm 18,000 mg/m3	OSHA P0
		STEL	30,000 ppm 54,000 mg/m3	OSHA P0

Biological occupational exposure limits

					I	
Components	CAS-No.	Control	Biological	Sam-	Permissible	Basis
		parameters	specimen	pling	concentra-	
				time	tion	
Methanol	67-56-1	Methanol	Urine	End of	15 mg/l	ACGIH
				shift (As	_	BEI
				soon as		
				possible		
				after		
				exposure		
				ceases)		
Toluene	108-88-3	Toluene	In blood	Prior to	0.02 mg/l	ACGIH
				last shift	_	BEI
				of work-		
				week		
		Toluene	Urine	End of	0.03 mg/l	ACGIH
				shift (As		BEI
				soon as		





Version Revision Date: SDS Number: Date of last issue: 09/06/2018 2.1 03/29/2023 600000001477 Date of first issue: 07/05/2018

				possible after exposure ceases)		
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI

Engineering measures : Provide sufficient mechanical (general and/or local exhaust)

ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or

apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an ap-

proved filter.

In the case of dust or aerosol formation use respirator with an

approved filter.

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment suppli-

er). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard

gloves that show tears, pinholes, or signs of wear.

Eye protection : Wear chemical splash goggles when there is the potential for

exposure of the eyes to liquid, vapor or mist.

Skin and body protection : Choose body protection according to the amount and con-

centration of the dangerous substance at the work place.

Wear as appropriate: Impervious clothing Flame-resistant clothing

Safety shoes

Remove and wash contaminated clothing before re-use.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

Avoid contact with skin, eyes and clothing.

When using do not smoke.

Wash hands before breaks and immediately after handling

the product.

When using do not eat or drink.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : aerosol

Melting point/freezing point : No data available





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/06/2018

 2.1
 03/29/2023
 600000001477
 Date of first issue: 07/05/2018

Boiling point/boiling range : No data available

Flash point : -20 °C

Method: closed cup Value for Component

Evaporation rate : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : No data available

Density : No data available

Solubility(ies)

Water solubility : No data available

Viscosity

Viscosity, kinematic : No data available

VOC % By Weight : 66 %

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed. Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks. Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

Strong oxidizing age Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Eye contact Skin contact Ingestion

Acute toxicity

Toxic if swallowed, in contact with skin or if inhaled.

Product:

Acute oral toxicity : Acute toxicity estimate: 299.39 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 8.06 mg/l

Exposure time: 4 h

Test atmosphere: vapour





Version Revision Date: SDS Number: Date of last issue: 09/06/2018 2.1 03/29/2023 600000001477 Date of first issue: 07/05/2018

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: 898.16 mg/kg

Method: Calculation method

Components:

Methanol:

Acute oral toxicity : LDLo (Humans): 300 mg/kg

Assessment: The component/mixture is toxic after single in-

gestion.

Acute inhalation toxicity : Test atmosphere: dust/mist

Assessment: The component/mixture is toxic after short term

inhalation.

Acute dermal toxicity : LD50 (Rabbit): 12,800 mg/kg

Assessment: The component/mixture is toxic after single con-

tact with skin.

Toluene:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat, males): 25.7 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 12,124 mg/kg

Acetone:

Acute oral toxicity : LD50 (Rat, female): 5,800 mg/kg

Acute inhalation toxicity : LC50 (Rat, female): 76 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 7,426 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks: May cause skin irritation and/or dermatitis.

Components:

Methanol:

Species: Rabbit

Result: No skin irritation

Toluene:

Result: Irritating to skin.





Version Revision Date: SDS Number: Date of last issue: 09/06/2018 2.1 03/29/2023 600000001477 Date of first issue: 07/05/2018

Acetone:

Result: Possibly irritating to skin

Result: Repeated exposure may cause skin dryness or cracking.

Carbon dioxide:

Assessment: No skin irritation Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

Methanol:

Species: Rabbit

Result: Possibly irritating to eyes

Toluene:

Result: Irritating to eyes.

Acetone:

Result: Irritating to eyes. Assessment: Irritating to eyes.

Carbon dioxide:

Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Methanol:

Test Type: Maximisation Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

Toluene:

Species: Guinea pig

Method: Directive 67/548/EEC, Annex V, B.6.



PRIMEGUARD® CARB CLEANER

Version Revision Date: SDS Number: Date of last issue: 09/06/2018 2.1 03/29/2023 600000001477 Date of first issue: 07/05/2018

Result: Not a skin sensitizer.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Suspected of damaging the unborn child.

Components:

Toluene:

Reproductive toxicity - As-

sessment

Some evidence of adverse effects on development, based on

animal experiments.

STOT - single exposure

May cause drowsiness or dizziness.

Causes damage to organs (Central nervous system, Eyes).

Components:

Methanol:

Target Organs: Central nervous system, Eyes

Assessment: The substance or mixture is classified as specific target organ toxicant, single ex-

posure, category 1.

Toluene:

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness.

Acetone:

Exposure routes: Inhalation Target Organs: Nervous system

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

May cause damage to organs (Neurologic: other (neuropsychological effects, auditory dysfunction and effects on color vision)) through prolonged or repeated exposure if inhaled.





Version Revision Date: SDS Number: Date of last issue: 09/06/2018 2.1 03/29/2023 600000001477 Date of first issue: 07/05/2018

Components:

Toluene:

Exposure routes: Inhalation

Target Organs: Neurologic: other (neuropsychological effects, auditory dysfunction and effects

on color vision)

Assessment: May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

Toluene:

May be fatal if swallowed and enters airways.

Acetone:

May be harmful if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

Additional ecological

information

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life.

Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR

UN/ID No. : UN 1950



PRIMEGUARD® CARB CLEANER

Version Date of last issue: 09/06/2018 Revision Date: SDS Number: 2.1 03/29/2023 60000001477 Date of first issue: 07/05/2018

Proper shipping name Aerosols, flammable

Class

Not assigned by regulation Packing group

Labels 2.1 Packing instruction (cargo 203

aircraft)

Packing instruction 203

(passenger aircraft)

IMDG-Code

UN number UN 1950 Proper shipping name **AEROSOLS**

Class 2.1

Packing group Not assigned by regulation

Labels 2.1 **EmS Code** F-D, S-U Marine pollutant

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number UN 1950 Proper shipping name Aerosols 2.1

Class

Packing group Not assigned by regulation

Labels 2.1 126 ERG Code Marine pollutant no

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Xylene	1330-20-7	100	100 (F003)
Xylene	1330-20-7	100	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation

Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard



NITEC

PRIMEGUARD® CARB CLEANER

Version Revision Date: SDS Number: Date of last issue: 09/06/2018 2.1 03/29/2023 600000001477 Date of first issue: 07/05/2018

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

Methanol 67-56-1 >= 30 - < 50 %

Toluene 108-88-3 >= 30 - < 50 %


California Prop. 65

WARNING: This product can expose you to chemicals including Benzene, Ethylbenzene, which is/are known to the State of California to cause cancer, and Methanol, Toluene, Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard

Revision Date : 03/29/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN