



Revision Number: 001.1

Issue date: 10/28/2014

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	Loctite® Extend® Rust Neutralizer	IDH number:	633877
Product type:	Rust converter	Item number:	633877
Restriction of Use:	None identified	Region:	United States
Company address:	Contact information:		
Henkel Corporation	Telephone: +1 (800) 624-7767		
One Henkel Way	MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-		
Rocky Hill, Connecticut 06067	4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY		
	Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887		

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: EXTREMELY FLAMMABLE AEROSOL.
 HARMFUL IF SWALLOWED.
 CAUSES SKIN IRRITATION.
 CAUSES SERIOUS EYE DAMAGE.
 MAY CAUSE DROWSINESS OR DIZZINESS.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE AEROSOL	1
ACUTE TOXICITY ORAL	4
SKIN IRRITATION	2
SERIOUS EYE DAMAGE	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3

PICTOGRAM(S)



Precautionary Statements

Prevention: Keep away from heat, sparks, open flames, hot surfaces - no smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing mist or spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear eye and face protection. Wear protective gloves.

Response: If SWALLOWED: Immediately call poison control or physician if you feel unwell. IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. Immediately call a poison control center or physician. Rinse mouth. If skin irritation occurs: Get medical attention. Take off contaminated clothing.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Acetone	67-64-1	30 - 60
2-Butoxyethanol	111-76-2	10 - 30
Polyvinyl butyral - polyvinyl alcohol - polyvinyl acetate terpolymer	27360-07-2	1 - 5
Formic acid	64-18-6	1 - 5
Propane/Isobutane	68476-86-8	10 - 30

* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Seek medical advice.
Skin contact:	Immediately wash skin thoroughly with soap and water. If symptoms develop and persist, get medical attention.
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. If symptoms develop and persist, get medical attention.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. If symptoms develop and persist, get medical attention.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Carbon dioxide. Dry chemical. foam
Special firefighting procedures:	Use water spray to keep fire exposed containers cool and disperse vapors. Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	Closed containers may rupture (due to build up of pressure) when exposed to extreme heat. Vapours may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back.
Hazardous combustion products:	Oxides of carbon. Hydrocarbons Butyraldehyde. Butyric acid. Acrolein. Aldehydes. Ketones. Organic acids.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow material to contaminate ground water system. Do not let product enter drains.
Clean-up methods:	Absorb the spilled material with an inert absorbent (nonflammable) material. Remove the absorbed material, and place in an appropriate chemical waste container for disposal. Eliminate ignition sources including sources of electrical, static or frictional sparks.

7. HANDLING AND STORAGE

Handling: Avoid breathing mists or aerosols of this product. Keep away from sources of ignition - no smoking. Avoid contact with eyes, skin and clothing. Keep out of the reach of children.

Storage: Contents under pressure. Do not handle or store near an open flame, heat or other sources of ignition. Do not puncture, incinerate, or expose to temperatures above 48.9 °C (120 °F). Store in a cool, dry, well-ventilated area.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Acetone	750 ppm STEL 500 ppm TWA	1,000 ppm (2,400 mg/m ³) PEL	None	None
2-Butoxyethanol	20 ppm TWA	50 ppm (240 mg/m ³) PEL (SKIN)	None	None
Polyvinyl butyral - polyvinyl alcohol - polyvinyl acetate terpolymer	None	None	None	None
Formic acid	5 ppm TWA 10 ppm STEL	5 ppm (9 mg/m ³) PEL	None	None
Propane/Isobutane	None	None	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Eye/face protection: Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid

Color: Light Grey

Odor: Acidic, Vinegar-like

Odor threshold: Not available.

pH: 3.0

Vapor pressure: Not available.

Boiling point/range: Not available.

Melting point/ range: Not available.

Specific gravity: 0.845 - 0.855

Vapor density: Not available.

Flash point: < -6.70 °C (< 19.94 °F)

Flashback: This product exhibits flashback when tested for flame extension.

Flammable/Explosive limits - lower: Not available.

Flammable/Explosive limits - upper: Not available.

Autoignition temperature: Not applicable

Evaporation rate: > 1.00

Solubility in water: Not available.

Partition coefficient (n-octanol/water): Not available.

VOC content: 33.1 %

Viscosity: Not available.

Decomposition temperature: Not available.

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: Will not occur.

Hazardous decomposition products: Oxides of carbon. Acrolein. Aldehydes. Ketones. Organic acids.

Incompatible materials: Oxidizing agents. Concentrated nitric acid. Sulfuric acid. Alkalis. Acids. Potassium tert-butoxide.

Reactivity: Not available.

Conditions to avoid: Keep away from open flames, hot surfaces and sources of ignition. Avoid temperatures above 49°C (120°F).

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation: Excessive inhalation of this material causes headache, dizziness, nausea and incoordination. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Skin contact: May cause skin irritation. Repeated or prolonged contact can result in drying of skin. Symptoms may include redness, burning, drying, cracking and skin burns.

Eye contact: Direct spray or vapors will irritate and may harm eyes. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Ingestion: Not a likely route of entry. May be harmful if swallowed. If swallowed, may be aspirated into the lungs resulting in inflammation and possible fluid accumulation.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Acetone	Oral LD50 (RABBIT) = 5,340 mg/kg Oral LD50 (RAT) = 5,800 mg/kg Oral LD50 (RAT) = 9,800 mg/kg Dermal LD50 (RABBIT) = 20,000 mg/kg Inhalation LC50 (RAT, 8 h) = 50.1 mg/l Inhalation LC50 (RAT, 4 h) = 76 mg/l	Blood, Central nervous system, Irritant, Reproductive
2-Butoxyethanol	Oral LD50 (RAT) = 560 mg/kg Oral LD50 (RABBIT) = 0.32 g/kg Oral LD50 (RAT) = 1.48 g/kg Dermal LD50 (RABBIT) = 400 mg/kg Inhalation LC50 (RAT, 4 h) = 486 ppm Inhalation LC50 (RAT, 4 h) = 450 ppm	Blood, Central nervous system, Irritant, Kidney, Liver
Polyvinyl butyral - polyvinyl alcohol - polyvinyl acetate terpolymer	None	No Records
Formic acid	Oral LD50 (RAT) = 730 mg/kg Inhalation LC50 (RAT, 15 min) = 15 mg/l Inhalation LC50 (RAT, 4 h) = 7.4 mg/l	Central nervous system, Corrosive, Irritant, Kidney, Metabolic
Propane/Isobutane	None	No Records

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Acetone	No	No	No
2-Butoxyethanol	No	No	No
Polyvinyl butyral - polyvinyl alcohol - polyvinyl acetate terpolymer	No	No	No
Formic acid	No	No	No
Propane/Isobutane	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:	Dispose of according to Federal, State and local governmental regulations.
Hazardous waste number:	It is the responsibility of the user to determine if an item is hazardous as defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics Leaching Procedure (TCLP) 40 CFR 261.20-24.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:	Aerosols, flammable
Hazard class or division:	2.1
Identification number:	UN 1950
Packing group:	None
DOT Hazardous Substance(s):	Acetone

International Air Transportation (ICAO/IATA)

Proper shipping name:	Aerosols, flammable
Hazard class or division:	2.1
Identification number:	UN 1950
Packing group:	None

Water Transportation (IMO/IMDG)

Proper shipping name:	AEROSOLS
Hazard class or division:	2.1
Identification number:	UN 1950
Packing group:	None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification:	None above reporting de minimis
CERCLA/SARA Section 302 EHS:	None above reporting de minimis
CERCLA/SARA Section 311/312:	Immediate Health, Delayed Health, Fire, Sudden Release
CERCLA/SARA Section 313:	This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). 2-Butoxyethanol (CAS# 111-76-2). Formic acid (CAS# 64-18-6).
California Proposition 65:	No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

CEPA DSL/NDL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.
-----------------------------	---

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

Prepared by: Mary Ellen Roddy, Sr. Regulatory Affairs Specialist

Issue date: 10/28/2014

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.