

**Safety Data Sheet**  
**MoliGuard**

**SECTION I - IDENTIFICATION**

**PRODUCT IDENTIFIER:** MoliGuard

**PRODUCT CODE:** 5440

**RECOMMENDED USE:** Dry Lubricant Spray

**RESTRICTIONS ON USE:** This product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.

**COMPANY NAME:** QuestSpecialty Corporation

**COMPANY ADDRESS:** P.O. Box 624, Brenham, TX 77834

**COMPANY PHONE:** 800-231-0454

**EMERGENCY PHONE:** 800-255-3924

**SECTION II – HAZARDS IDENTIFICATION**

**CLASSIFICATION:** Flammable Aerosol: Category 1

Liquefied Gas

Skin Irritant: Category 2

Eye Irritant: Category 2A

Carcinogenicity: Category 2

Specific Target Organ Toxicity (Single Exposure): Category 3

Specific Target Organ Toxicity (Repeated Exposure): Category 2

**HAZARD STATEMENT(S): DANGER:** Extremely Flammable Aerosol. Contains gas under pressure; May explode if heated. Causes skin and serious eye irritation. Suspected of causing cancer. May cause respiratory irritation, drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.

This product contains the following percentage of chemicals of unknown toxicity: 0%

**PRECAUTIONARY STATEMENTS:** Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wear protective gloves and eye protection. Wash hands thoroughly after handling. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical advice or attention. Avoid breathing mist, fumes, or spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. Dispose of contents and container in accordance with local, state, and national regulations.

**SYMBOL:**



**HAZARDS NOT OTHERWISE CLASSIFIED:** N/A

**SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS**

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Methylene Chloride	75-09-2	60-100%
Propane/n-Butane	68476-86-8	10-30%
Isopropyl Alcohol	67-63-0	3-7%

**SECTION IV - FIRST AID MEASURES**

**EYES:** Remove contact lenses. Flush with water for at least 15 minutes. Get immediate medical attention

**INGESTION:** Rinse mouth with water. Do not induce vomiting unless directed by medical authority. Seek medical attention if irritation persists.

**Safety Data Sheet**  
**MoliGuard**

**INHALATION:** Move to fresh air. If breathing is difficult, administer oxygen. If not breathing administer artificial respiration or at any sign of loss of consciousness seek immediate medical attention.

**SKIN:** Immediately wash with soap and water for 15 minutes. Remove contaminated clothing and shoes immediately. Seek medical attention if irritation develops.

**ACUTE HEALTH HAZARDS:** Eyes: redness, tearing, blurred vision

Skin: defatting and dermatitis

Inhalation: Irritation

Oral: abdominal irritation, nausea, vomiting, and diarrhea

**CHRONIC HEALTH HAZARDS:** Possible cancer causing agent and overexposure may also include damage to kidneys, liver, dizziness, headache, nausea, mental confusion, visual disturbances, dermatitis, lungs, blood, or central nervous system.

**NOTE TO PHYSICIAN:** Do not administer adrenaline or epinephrine to a victim of chlorinated solvent poisoning. This product contains ingredients that may be anticipated to be a carcinogen.

**SECTION V – FIRE-FIGHTING MEASURES**

**EXTINGUISHING MEDIA:** Dry chemical, foam, or Carbon Dioxide (CO<sub>2</sub>).

**UNSUITABLE EXTINGUISHING MEDIA:** Water spray/stream.

**SPECIAL FIRE FIGHTING PROCEDURES:** Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Contents under pressure. Exposure to temperatures above 120°F may cause bursting. Flammable.

**HAZARDOUS COMBUSTION PRODUCTS:** Oxides of carbon, chlorine, hydrogen chloride and phosgene.

**SECTION VI – ACCIDENTAL RELEASE MEASURES**

**PERSONAL PROTECTIVE EQUIPMENT:** Refer to section VIII for proper Personal Protective Equipment.

**SPILL:** Contain spill, eliminate ignition sources and ventilate area. Prevent spill from entering sewers, storm drains, and natural waterways. Use non-combustible material like vermiculite, sand or earth for larger spills.

**WASTE DISPOSAL:** Dispose of contents in accordance with federal, state, and local regulations. Do not dump in sewers. Wrap container and place in trash collection, do not puncture, incinerate, or reuse container.

**RCRA STATUS:** Waste likely considered hazardous under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

**SECTION VII – HANDLING AND STORAGE**

**HANDLING AND STORAGE:** Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store locked up.  
Pressurized container: Do not pierce or burn, even after use.

**OTHER PRECAUTIONS:** Keep out of the reach of children.

**INCOMPATIBILITY:** Some plastics and painted surfaces, pre-test before using.

**SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION**

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Methylene Chloride	25 ppm	50 ppm
Propane/n-Butane	1000 ppm	1000 ppm
Isopropyl Alcohol	400 ppm	200 ppm

**ENGINEERING CONTROLS / VENTILATION:** General ventilation and local exhaust may be required to meet TLV requirements.

**RESPIRATORY PROTECTION:** Wear NIOSH/MSHA approved respiratory protection if exposure limits are exceeded.

**PERSONAL PROTECTIVE EQUIPMENT:** Safety glasses and chemical resistant gloves

**ADDITIONAL MEASURES:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

**SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES**

**APPEARANCE:** Black Spray

**ODOR:** Chlorinated solvent odor

**Safety Data Sheet**  
**MoliGuard**

**ODOR THRESHOLD:** N/D  
**pH:** N/A  
**MELTING POINT/FREEZING POINT:** N/D  
**INITIAL BOILING POINT AND BOILING RANGE:** N/D  
**FLASH POINT:** N/D  
**EVAPORATION RATE:** >7  
**FLAMMABILITY(solid/gas):** Extremely Flammable Aerosol  
**UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:**  
    **LOWER FLAMMABILITY LIMIT:** N/D  
    **UPPER FLAMMABILITY LIMIT:** N/D  
    **EXPLOSIVE LIMIT LOWER (%):** N/D  
    **EXPLOSIVE LIMIT UPPER (%):** N/D  
**VAPOR PRESSURE (mm Hg):** 350 mm Hg @ 20°C  
**VAPOR DENSITY (AIR=1):** 2.93  
**RELATIVE DENSITY (H<sub>2</sub>O=1):** 1.29 @ 77° F (25°C)  
**SOLUBILITY(IES):** Immiscible in water  
**PARTITION COEFFICIENT: n-OCTANOL/WATER (K<sub>ow</sub>):** N/D  
**AUTOIGNITION TEMPERATURE:** N/D  
**DECOMPOSITION TEMPERATURE:** N/D  
**VISCOSITY:** N/D

**SECTION X – STABILITY AND REACTIVITY**

**REACTIVITY:** None Known  
**CHEMICAL STABILITY:** Stable  
**POSSIBLE HAZARDOUS REACTIONS:** None Known  
**CONDITIONS TO AVOID:** Temperatures greater than 122°F and sources of ignition.  
**INCOMPATIBLE MATERIALS:** Some plastics and painted surfaces, pre-test before using.  
**HAZARDOUS DECOMPOSITION PRODUCTS:** Oxides of carbon, chlorine, hydrogen chloride and phosgene.

**SECTION XI – TOXICOLOGICAL INFORMATION**

**TOXICOLOGICAL INFORMATION:** **Methylene Chloride (75-09-2):** LD<sub>50</sub> (Oral, Rat) >2000 mg/kg. LD<sub>50</sub> (Dermal Rat) >2000 mg/kg. LC<sub>50</sub> (Inhalation, Rat) 52000 mg/m<sup>3</sup>.  
**ROUTES OF ENTRY:** Eyes, Ingestion, Inhalation, Skin  
**EYES:** Causes irritation, burning, redness, tearing.  
**INGESTION:** Ingestion of product may result in vomiting; aspiration (breathing) of vomitus into the lungs must be avoided as even small quantities may result in aspiration pneumonitis  
**INHALATION:** Irritation to respiratory tract, dizziness, headache, nausea, depression of central nervous system, prolonged exposure may cause unconsciousness, heart effects, liver effects, kidney effects, and death.  
**SKIN:** Causes localized defatting, irritation, may be absorbed through skin with systemic effects.  
**MEDICAL CONDITION AGGRAVATED:** Excessive exposure will aggravate pre-existing skin disorders, respiratory, liver, kidney, cardiovascular or pulmonary illnesses.  
**ACUTE HEALTH HAZARDS:** Eyes: redness, tearing, blurred vision  
Skin: defatting and dermatitis  
Inhalation: Irritation  
Oral: abdominal irritation, nausea, vomiting, and diarrhea  
**CHRONIC HEALTH HAZARDS:** Possible cancer causing agent and overexposure may also include damage to kidneys, liver, dizziness, headache, nausea, mental confusion, visual disturbances, dermatitis, lungs, blood, or central nervous system.  
**CARCINOGENICITY:** OSHA: Yes ACGIH: A3 - Animal Carcinogen NTP: Suspected IARC: 2B - Possible OTHER: CA Prop 65

**SECTION XII – ECOLOGICAL INFORMATION**

**ECOTOXICITY:** Not Established  
**PERSISTENCE AND DEGRADABILITY:** Component or components of this product are not biodegradable.  
**BIOACCUMULATIVE POTENTIAL:** This product is not expected to bioaccumulate.  
**MOBILITY IN SOIL:** This product is mobile in soil.  
**OTHER ADVERSE EFFECTS:** None Known

**Safety Data Sheet**  
**MoliGuard**

**SECTION XIII – DISPOSAL CONSIDERATIONS**

**WASTE DISPOSAL:** Dispose of contents in accordance with federal, state, and local regulations. Do not dump in sewers. Wrap container and place in trash collection, do not puncture, incinerate, or reuse container.  
**RCRA STATUS:** Waste likely considered hazardous under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

**SECTION XIV - TRANSPORT INFORMATION**

**PROPER SHIPPING NAME:** Aerosols, Ltd. Qty.  
**HAZARD CLASS/DIVISION:** 2.1  
**UN/NA NUMBER:** UN 1950  
**PACKING GROUP:** N/A

**AIR SHIPMENT**

**PROPER SHIPPING NAME:** Aerosols, Flammable, Containing Substances in Division 6.1 Packing Group III  
**HAZARD CLASS/DIVISION:** 2.1 (6.1)  
**UN/NA NUMBER:** UN 1950  
**PACKING GROUP:** N/A

**SHIPPING BY WATER:**

**VESSEL (IMO/IMDG)**  
**PROPER SHIPPING NAME:** Aerosols  
**HAZARD CLASS/DIVISION:** 2.1 (6.1)  
**UN/NA NUMBER:** UN 1950  
**PACKING GROUP:** N/A  
**ENVIRONMENTAL HAZARDS WATER:** N/A

**SECTION XV - REGULATORY INFORMATION**

**TSCA STATUS:** All Chemicals are listed or exempt.  
**CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT):** Methylene Chloride (75-09-2)  
Reportable Quantity = 1,000 lbs  
**SARA 311/312 HAZARD CATEGORIES:** Acute Health, Chronic Health.  
**SARA 313 REPORTABLE INGREDIENTS:** Methylene Chloride - 75-09-2  
**STATE REGULATIONS:** This product can expose you to chemicals including Dichloromethane, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov). **Methylene Chloride (75-09-2) RTK:** MA, NJ, PA  
**INTERNATIONAL REGULATIONS:** All components are listed or exempted.  
**VOLATILE ORGANIC COMPOUNDS (VOC):** 24%  
This product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.

<b>NFPA HEALTH:</b>	3	<b>HMIS HEALTH:</b>	3
<b>NFPA FLAMMABILITY:</b>	3	<b>HMIS FLAMMABILITY:</b>	3
<b>NFPA REACTIVITY:</b>	1	<b>HMIS REACTIVITY:</b>	1
<b>NFPA OTHER:</b>	None	<b>HMIS PROTECTION:</b>	B

6.31# Methylene Chloride per case

**SECTION XVI - OTHER INFORMATION**

**PREPARATION BY:** Andrew Bach  
**DATE PREPARED:** 8/21/2013  
**REVISION DATE:** 05/23/2019

N/A = Not Applicable; N/D = Not Determined

## Safety Data Sheet

### MoliGuard

**DISCLAIMER:** To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.