

Safety Data Sheet

LOCTITE 242

Page 1 of 9

SDS No.: 150233

V001.6

Date of issue: 18.09.2020

respiratory tract irritation

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE 242

Supplier:

Henkel Australia Pty Ltd 135-141 Canterbury Road Kilsyth, Victoria, 3137

Australia

Phone: +61 (3) 9724 6444

Emergency information: 24 HOUR EMERGENCY CONTACT NUMBER: 1800 032 379

Section 2. Hazards identification

Classification of the substance or mixture

Hazardous according to the criteria of Safe Work Australia.

GHS Classification:

Hazard Class Hazard Category Target organ Category 2A

Serious eye irritation Target Organ Systemic Toxicant -

Single exposure

Acute hazards to the aquatic

environment

Chronic hazards to the aquatic

environment

Category 3 Category 3

Category 3

Hazard pictogram:

Signal word:

Warning

SDS No.: 150233 Page 2 of 9

V001.6 LOCTITE 242

Hazard statement(s): H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statement(s):

Prevention: P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment. P280 Wear eye protection/face protection.

Response: P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

Storage: P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal: P501 Dispose of contents/container to an appropriate treatment and disposal facility in

accordance with applicable laws and regulations.

Dangerous Goods information:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Section 3. Composition / information on ingredients

General chemical description: Mixture

Type of preparation: Anaerobic Sealant

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
Polyethylene glycol 200 dimethacrylate	25852-47-5	50- < 80 %
Propane-1,2-diol	57-55-6	< 10 %
α, α-dimethylbenzyl hydroperoxide	80-15-9	1-< 3 %
1,4-Naphthalenedione	130-15-4	< 1 %
non hazardous ingredients~		20- < 70 %

Section 4. First aid measures

Ingestion: Do not induce vomiting.

Have victim rinse mouth thoroughly with water.

Seek medical advice.

Skin: In case of contact, immediately remove contaminated clothing and flush skin with copious

amounts of water. Seek medical advice.

Eyes: Wash with plenty of water immediately and continue for several minutes, holding eyelid

open. Consult a doctor.

Inhalation: Move to fresh air in case of accidental inhalation of vapours.

Seek medical advice.

First Aid facilities: Eye wash and safety shower

Normal washroom facilities

SDS No.: 150233 Page 3 of 9

V001.6 LOCTITE 242

Medical attention and special

treatment:

Treat symptomatically and supportively.

Section 5. Fire fighting measures

Suitable extinguishing media: Carbon dioxide, foam, powder

Decomposition products in case of

fire:

Thermal decomposition can lead to release of irritating gases and vapors.

carbon monoxide Carbon dioxide. Oxides of nitrogen. Oxides of sulfur.

Special protective equipment for

fire-fighters:

Wear full protective clothing.

Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).

Additional fire fighting advice: In case of fire, keep containers cool with water spray.

Collect contaminated fire fighting water separately. It must not enter drains.

Section 6. Accidental release measures

Personal precautions: Avoid skin and eye contact.

Danger of slipping on spilled product.

Wear protective equipment. Ensure adequate ventilation.

Use personal protective equipment as described in Section 8.

Environmental precautions: Waste disposal with the approval of the responsible local authority.

Do not discharge into surface water/ground water.

Clean-up methods: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder,

sawdust).

Scrape up spilled material and place in a closed container for disposal.

Section 7. Handling and storage

Precautions for safe handling: Use only in well-ventilated areas.

Avoid skin and eye contact.

Wear suitable protective clothing, safety glasses and gloves.

Conditions for safe storage: Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to

containers as contamination may reduce the shelf life of the bulk product.

Unsuitable materials with

product:

plastic

Section 8. Exposure controls / personal protection

National exposure standards:

Ingredient [Regulated substance]	form of exposure	TWA (ppm)	TWA (mg/m3)	Peak Limit.	Peak Limit. (mg/m3)	STEL (ppm)	STEL (mg/m3)
SILICA, AMORPHOUS: FUMED SILICA (RESPIRABLE DUST)	Respirable dust.		2	(PP)	((
112945-52-5							

SDS No.: 150233 Page 4 of 9

V001.6 LOCTITE 242

FUMED SILICA (RESPIRABLE DUST) 112945-52-5	Respirable dust.		2		
PROPANE-1,2-DIOL TOTAL: (VAPOUR & PARTICULATES) 57-55-6	Total vapour and particulates.	150	474		
PROPANE-1,2-DIOL: PARTICULATES ONLY 57-55-6	Particulate.		10		

None

Engineering controls: Ensure good ventilation/suction at the workplace.

Eye protection: Wear protective glasses.

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk

of splashing.

Skin protection: Wear suitable protective clothing.

Recommended gloves include butyl rubber and neoprene.

Use chemical resistant, impervious gloves and clothing to prevent skin contact. Please note that in practice the working life of chemical resistant gloves may be

considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed

then the gloves should be replaced.

Respiratory protection: If inhalation risk exists, wear a respirator or air supplied mask complying with the

requirements of AS/NZS 1715 and AS/NZS 1716.

Section 9. Physical and chemical properties

Appearance: blue liquid

Odor: mild

pH: Not applicable

Specific gravity: 1.1

Boiling point: > 149.0 °C (> 300.2 °F) **Flash point:** > 93.3 °C (> 199.94 °F)

(Tagliabue closed cup)

Vapor pressure: < 6.67 mbar

(; 27 °C (80.6 °F))

Viscosity (dynamic): 800 - 1,600 mPa.s

(BROOKFIELD WITH HELIPATH; Instrument: RVF, HELIPATH; 25 °C (77 °F); speed of rotation: 20 min-1; Spindle No: 3; Method: ;; LCT STM 10; Viscosity Brookfield)

VOC content: 0.56 % 6.17 g/l

Section 10. Stability and reactivity

Stability: Stable under normal conditions of temperature and pressure.

Conditions to avoid: Avoid excessive heat and ignition sources.

Extremes of temperature.

SDS No.: 150233 Page 5 of 9

V001.6 LOCTITE 242

Incompatible materials: Strong oxidizing agents.

Acids and bases. Reducing agents.

Hazardous decomposition

products:

Thermal decomposition can lead to release of irritating gases and vapors.

carbon monoxide Carbon dioxide. Oxides of sulfur. Oxides of nitrogen.

Hazardous polymerization: Will not occur.

Section 11. Toxicological information

Health Effects:

Ingestion: May cause mild gastrointestinal irritation with nausea, vomiting, diarrhea and abdominal pain.

Skin: May cause mild skin irritation. **Eyes:** Causes serious eye irritation.

Symptoms may include severe irritation, pain, tearing, blurred vision.

Inhalation: Causes respiratory tract irritation.

Vapors may cause irritation of the nose, throat, and respiratory tract.

Acute toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Polyethylene glycol 200 dimethacrylate 25852-47-5	LD50	> 5,000 mg/kg	oral		rat	not specified
Propane-1,2-diol	LD50	22,000 mg/kg	oral		rat	not specified
57-55-6	LC50	> 317.042 mg/l	inhalation	2 h	rabbit	not specified
	LD50	> 2,000 mg/kg	dermal		rabbit	not specified
α, α-dimethylbenzyl	LD50	382 mg/kg	oral		rat	other guideline:
hydroperoxide	LD50	530 - 1,060			rat	other guideline:
80-15-9	Acute	mg/kg	dermal			Expert judgement
	toxicity	1,100 mg/kg	dermal			
	estimate					
	(ATE)					
1,4-Naphthalenedione 130-15-4	LD50	190 mg/kg	oral		rat	not specified

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Propane-1,2-diol 57-55-6	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
α, α-dimethylbenzyl hydroperoxide 80-15-9	corrosive		rabbit	Draize Test

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Propane-1,2-diol	not irritating		rabbit	OECD Guideline 405 (Acute
57-55-6				Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Hazardous components	Result	Test type	Species	Method
CAS-No.				
Propane-1,2-diol	not sensitising	Guinea pig	guinea pig	equivalent or similar to OECD
57-55-6	-	maximisat		Guideline 406 (Skin
		ion test		Sensitisation)

Page 6 of 9 SDS No.: 150233 LOCTITE 242

V001.6

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Propane-1,2-diol 57-55-6	negative negative	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test	without with and without		Ames Test OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Propane-1,2-diol 57-55-6	negative negative negative	oral: gavage intraperitoneal oral: gavage		rat mouse rat	not specified not specified not specified
α, α-dimethylbenzyl hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
α, α-dimethylbenzyl hydroperoxide 80-15-9	negative	dermal		mouse	not specified

Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Propane-1,2-diol 57-55-6	NOAEL=1,700 mg/kg	oral: feed	2 yearsdaily	rat	not specified
Propane-1,2-diol 57-55-6	NOAEL=1000 mg/m3	inhalation	90 d6 h/d, 5 d/w	rat	not specified
α, α-dimethylbenzyl hydroperoxide 80-15-9		inhalation: aerosol	6 h/d5 d/w	rat	not specified

Section 12. Ecological information

SDS No.: 150233 Page 7 of 9

V001.6 LOCTITE 242

General ecological information: Do not empty into drains / surface water / ground water.

Ecotoxicity: Harmful to aquatic life with long lasting effects.

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity	Exposure time	Species	Method
CAS-IVO.	туре		Study	ume		
Polyethylene glycol 200 dimethacrylate 25852-47-5	LC50	> 10 - 100 mg/l	Fish	96 h	not specified	OECD Guideline 203 (Fish, Acute Toxicity Test)
Polyethylene glycol 200 dimethacrylate 25852-47-5	EC0	> 10 - 100 mg/l	Bacteria	3 h	not specified	OECD Guideline 209 (Activated Sludge, Respiration
Propane-1,2-diol 57-55-6	LC50	> 10,000 mg/l	Fish	48 h	Leuciscus idus	Inhibition Test) DIN 38412-15
Propane-1,2-diol 57-55-6	EC50	18,340 mg/l	Daphnia	48 h	Ceriodaphnia dubia	other guideline:
Propane-1,2-diol 57-55-6	EC50	24,200 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Propane-1,2-diol 57-55-6	NOEC	15,000 mg/l	Algae	14 d	Pseudokirchneriella subcapitata	
Propane-1,2-diol 57-55-6	EC50	> 1,000 mg/l	Bacteria	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration
α, α-dimethylbenzyl hydroperoxide 80-15-9	LC50	3.9 mg/l	Fish	96 h	Oncorhynchus mykiss	Inhibition Test) OECD Guideline 203 (Fish, Acute Toxicity Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	EC50	18 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	ErC50	3.1 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	,
α, α-dimethylbenzyl hydroperoxide 80-15-9	EC10	70 mg/l	Bacteria	30 min		not specified
1,4-Naphthalenedione 130-15-4	EC50	0.011 mg/l	Algae	72 h	Dunaliella bioculata	OECD Guideline 201 (Alga, Growth Inhibition Test)

Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Polyethylene glycol 200 dimethacrylate 25852-47-5	readily biodegradable	aerobic	> 60 %	OECD 301 A - F
Propane-1,2-diol 57-55-6	not inherently biodegradable	aerobic	60 %	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
Propane-1,2-diol 57-55-6	readily biodegradable	aerobic	> 81.7 - 100 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9		no data	0 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
1,4-Naphthalenedione 130-15-4	not readily biodegradable.	no data	0 - 60 %	OECD 301 A - F

Bioaccumulative potential / Mobility in soil:

Hazardous components	LogPow	Bioconcentration	Exposure	Species	Temperature	Method
CAS-No.		factor (BCF)	time			

SDS No.: 150233 Page 8 of 9

V001.6 LOCTITE 242

Propane-1,2-diol 57-55-6	-1.07			20.5 °C	EU Method A.8 (Partition Coefficient)
α, α-dimethylbenzyl hydroperoxide 80-15-9		9.1	calculation		OECD Guideline 305 (Bioconcentration: Flow- through Fish Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	2.16				not specified
1,4-Naphthalenedione 130-15-4	1.71				not specified

Section 13. Disposal considerations

Waste disposal of product: Dispose of in accordance with local and national regulations.

Disposal for uncleaned package: After use, tubes, cartons and bottles containing residual product should be disposed of as

chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Section 14. Transport information

Road and Rail Transport:

Dangerous Goods information: Not classified as Dangerous Goods according to the criteria of the

Australian Code for the Transport of Dangerous Goods by Road and

Rail (ADG Code).

Marine transport IMDG:

Not dangerous goods

Air transport IATA:

Not dangerous goods

Section 15. Regulatory information

SUSMP Poisons Schedule None

Section 16. Other information

Abbreviations/acronyms: ADGC - Australian Dangerous Goods Code

GHS: Globally Harmonized System CAS: Chemical Abstracts Service

OECD: Organization for Economic Cooperation and Development

LD 50: Lethal Dose 50%

LC 50: Lethal Concentration 50%

IMDG: International Maritime Dangerous Goods code

IATA-DGR: International Air Transport Association - Dangerous Goods Regulations

Reason for issue: Reviewed SDS. Reissued with new date. involved chapters: 1,2,3,6.8,9,15,16

SDS No.: 150233 Page 9 of 9

V001.6 LOCTITE 242

Date of previous issue: 21.10.2015

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.

The information contained in the Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.